Calibration of the Rossi X-ray Timing Explorer Proportional Counter Array

Keith Jahoda¹, Craig B. Markwardt¹, ², Yana Radeva³, Arnold H. Rots⁴, Michael J. Stark⁵, Jean H. Swank¹, Tod E. Strohmayer¹, and William Zhang¹

keith.m.jahoda@nasa.gov

ABSTRACT

We present the calibration and background model for the Proportional Counter Array (PCA) aboard the Rossi X-ray Timing Explorer (RXTE). The energy calibration is systematics limited below 10 keV with deviations from a power law fit to the Crab nebula plus pulsar less than 1%. Unmodelled variations in the instrument background amount to less than 2% of the observed background below 10 keV and less than 1% between 10 and 20 keV. Individual photon arrival times are accurate to $4.4\mu s$ at all times during the mission and to $2.5\mu s$ after 29 April 1997. The peak pointing direction of the five collimators is known at few arcsec precision.

Subject headings: instrumentation: detectors – space vehicles: instruments

1. Introduction

The Proportional Counter Array (PCA) aboard the Rossi X-ray Timing Explorer (RXTE) consists of 5 large area proportional counters designed to perform high resolution timing and modest spectral observations of bright X-ray sources. With a 1° collimator (FWHM) and well

¹GSFC/LHEA Code 662, Greenbelt, MD 20771

²Univ. of MD, College Park, MD

³Connecticut College, New London, CT

³Harvard Smithsonian Center for Astrophysics, Cambridge, MA

⁴Lafavette College, Easton, PA

modelled background, the PCA is confusion limited at fluxes of $\approx 4 \times 10^{-12}\,\mathrm{erg\,sec^{-1}\,cm^{-2}}$ in the 2-10 keV band (approximately 0.3 count $\mathrm{sec^{-1}\,PCU^{-1}}$) and is capable of observing sources with fluxes up to 20,000 counts $\mathrm{sec^{-1}\,PCU^{-1}}$. The primary focus of this paper is the energy and background calibration of the PCA. The response matrix generator and default parameters are those included in the FTOOLS software package v5.3 release¹. The background models presented² are available from the RXTE Guest Observer Facility. We also summarize calibration information related to the deadtime, absolute timing, pointing, and collimator field of view of the PCA.

This paper presents calibration information relevant to scientific users of the RXTE PCA. The paper is organized as follows: Section 2 gives an overview of the instrument and its operations. Section 3 describes the elements of the response matrix, including a description of the parameters which are supplied to the response matrix generator pcarmf. Section 4 describes the use of on-orbit data to determine the best values of the response matrix parameters and presents the resulting fits to spectra from the Crab nebula and the Iron line in Cas-A. Section 5 describes the method used to construct the background model and describes the results. Section 6 describes the effects of deadtime in the PCA and how to correct for deadtime. Section 7 describes the absolute timing accuracy. Section 8 documents the relative pointing of the PCU collimators and decribes the model of the PCA collimators. References to specific tools or parameters are to those included in the v5.3 release of the FTOOLS unless otherwise noted. Modest updates, particularly to calibrate the energy scale at future times, may be expected in future releases; the most current values should be available via the High Energy Astrophysics Science and Archival Research Center (HEASARC) Calibration Data base.

2. Instrument Description

The PCA consisits of 5 nominally identical Proportional Counter Units (PCU). Each has a net geometric collecting area of $\sim 1600\,\mathrm{cm^2}$. Construction, ground performance, and early inflight performance are described elsewhere (Glasser et al. 1994; Zhang et al. 1993; Jahoda et al. 1996). The proportional counters were designed, built, and tested within the Goddard Space Flight Center (GSFC) Laboratory for High Energy Astrophysics. The essential features Zhang et al. (1993, figures 1 and 2) are a mechanical collimator with FWHM $\sim 1^\circ$, an aluminized mylar window, a propane filled "veto" volume, a second mylar

¹http://heasarc.gsfc.nasa.gov/ftools/

²pca_bkgd_cmfaintl7_eMv20031123.mdl and pca_bkgd_cmbrightvle_eMv20030330.mdl.

window, and a Xenon filled main counter. The Xenon volume is divided into cells of $\sim 1\,\mathrm{cm} \times 1\,\mathrm{cm} \times 1\mathrm{m}$ by wire walls. The detector bodies are constructed of Aluminum and surrounded by a graded shield consisting of a layer of Tin followed by a layer of Tantalum. Nominal dimensions are given in table 1. There are three layers of Xenon cells, and each layer is divided in half by connecting alternate cells to either the "right" or "left" amplifier chain. The division of each layer is significant for data screening and background modelling. The response matrices for each half of each layer are identical. Scientific analyses generally combine data from the two halves.

Every event, whether due to background or a cosmic source, passes 19 bits over a serial interface to the Experiment Data System (EDS) ³. The information includes 8 bits of pulse height for events occuring on the Xenon signal or propane veto layers, 2 bits of pulse height for events on the Xenon veto layer, 8 lower level discriminator bits and a very large event flag. The EDS applies a time-tag and performs event selection and (multiple) data compressions. Of particular interest, two standard compression modes have been run throughout the entire mission. Standard 1 provides light curves with 0.125 sec resolution and calibration spectra with full pulse height information collected every 128 seconds. Standard 2 provides pulse height information for each layer of each detector with 16 second resolution and 29 rates which account for all the "non X-ray" events. Both Standard modes count each event produced by the PCA exactly once. Data used for in-flight calibration of the energy scale comes exclusively from the standard modes. Scientific data in the telemetry stream identifies the detectors with a 0-4 scheme. ⁴

2.1. Routine Operations

The RXTE spacecraft allows extremely flexible observations, often making more than 20 discrete and scientifically motivated pointings within a day. The data modes are selectable, allowing the compression which is required for bright objects (due to downlink bandwidth) to be performed in a user selected way. More detail about the standard and user selectable data modes is contained in the RXTE user guide. A brief description of creating response matrices for user selected modes, using the ftool pcarsp, is given in the Appendix. Throughout this paper we use a typewriter font to refer to FTOOLS programs and an *italic* font to refer to

³The EDS was designed and built at the MIT Center for Space Research. A functional description is provided in the RXTE user guide at http://heasarc.gsfc.nasa.gov/docs/xte/appendix_f.html

⁴Much of the engineering and housekeeping data uses a 1-5 numbering scheme. All references to inidividual PCUs in this paper use the 0-4 convention.

the associated parameters.

In addition to pointing direction and data compression mode, there are only two user commandable parameters.

Each detector is equipped with a High Rate Monitor (HRM) which disables the high voltage when the total number of counts on any anode exceeds a preset counting rate for 3 consecutive 8 second intervals. The default is set to 8000 count sec⁻¹. This rate is occasionally adjusted upwards (typically to 24,000 count sec⁻¹) for observations of extremely bright sources such as Sco X-1. It is unlikely that the HRM would ever be tripped if set much above 35,000 count sec⁻¹ as paralyzable deadtime losses prevent the detector from registering more than about this counting rate.

Each detector is also equiped with a selectable Very Large Event window. Events which saturate the pre-amplifiers cause ringing as the amplifier relaxes towards the baseline; often the ringing can cause false events to be pushed through the system. The timing of these events is dependent on the actual pulse height of the saturating event. Each detector has 4 commandable windows, set nominally to 20, 60, 150, and 500μ s. The pre-launch intention was to allow "extra clean data" for very faint sources and "high throughput" data for very bright sources. The size of the VLE window affects the shape of the power spectrum (section 6.1). Early observations of Cyg X-1 with the VLE window set to the smallest value demonstrated a failure associated with this window on one of the analog chains; use of the shortest VLE window has been discontinued. The third window is the default; observations of some bright sources have been conducted with the second window. The calibrated values of these two windows are 70 and 170μ s.

The High Voltage is commandable in discrete steps, and has been changed by the instrument team 3 times during the mission, resulting in discontinuities in the energy response. In addition, the propane layer in PCU 0 lost pressure in the spring of 2000, in a manner consistent with a micro-meteorite induced pinhole. We use the term epoch to describe the periods between these discontinuous changes in the instrument response. Response changes within an epoch are gradual and can be described by parameterizations with a small time dependence. Definitions of the epochs are given in Table 2. Epoch 3 is divided into 3A and 3B as the time dependence of the background model changed significantly within epoch 3; the boundary is near the moment when orbital decay became important as discussed in section 5.

Three of the PCUs became subject to periodic breakdowns after launch. This behaviour began in March 1996 for PCUs 3 and 4 and in March 1999 for PCU 1. To minimize breakdowns several operational steps were taken. First, detectors that break down are now cycled

off and on and are not used when the scientific objectives do not require large instantaneous area. Second, the high voltage has been lowered. Finally, the spacecraft roll angle has been changed slightly to increase the solar heating of the PCU and to operate at a slightly warmer temperature. While breakdowns still occur, the EDS detects these occurrences by comparing the first moment of the pulse height distributions from the two anode chains associated with each layer. When mismatched moments are detected, the EDS sets a status signal detectable in the satellite Telemetry Status Monitoring (TSM) system which causes the high voltage to be turned off. The EDS calculation is performed every 16 sec; the TSM requires 5 consecutive readings (separated by 8 sec), so periods of breakdown are limited to less than 45 seconds; resting the detectors for a few hours allows them to be turned on again. In mid-2004, the duty cycles of PCUs 0-4 were $\sim 1.0, 0.1, 1.0, 0.3,$ and 0.1.

The high voltage was lowered in March 1996 and again in April 1996 as new operating procedures were installed after the first breakdowns of PCU 3 and 4. The high voltage was lowered again in April 1999 after the first breakdown in PCU 1. The times are given in Table 2 along with the high voltage settings (pre-launch measurements) within the Xenon detectors.

There was a brief period in March 1999 when the high voltage fluctuated from the desired setting (level 4) to the epoch 3 setting (level 5) due to an error in the high voltage commanding surrounding the South Atlantic Anomaly. The archived PCA housekeeping data correctly records the instantaneous high voltage state.

3. Response Matrix Overview

The response matrix provides the information about the probability that an incident photon of a particular energy will be observed in a particular instrument channel. The PCA response matrices are generated within the standard FTOOLS environment (Blackburn 1995) ⁵ and are designed for use with the XSPEC convolution and spectral model fitting program (Arnaud 1996) ⁶. A satisfactory matrix must account for

- The energy to mean channel relationship
- the quantum efficiency as a function of energy

⁵http://heasarc.gsfc.nasa.gov/ftools/

⁶http://heasarc.gsfc.nasa.gov/lheasoft/

• the spectral redistribution within the detector

We describe below the model as implemented by the program pcarmf as released in FTOOLS v5.3 in November 2003. The ftool pcarmf produces a 256 channel response matrix for a single detector or detector layer. The appendix describes the additional steps needed to produce a response matrix any of the rebinned and compressed modes commonly used by the PCA and found in the RXTE archive.

3.1. Energy to channel model

The energy to channel relationship in proportional counters is non-monotonic in the neighborhood of atomic absorption edges (Jahoda and McCammon 1988; Bavdaz et al. 1995; Tsunemi et al. 1993). The mean ionization state of an atom which absorbs a photon just above an atomic absorption edge is greater than the mean ionization state if the photon is just below the edge. Because more energy goes into potential energy assoicated with the absorbing atom, the photo-electron (and other electrons electrons ejected from the atom by Auger or shake-off processes) have less kinetic energy and the mean number of electrons produced in the absorbing gas is smaller. Between edges, the energy available for ionizing the gas increases smoothly as does the mean number of electrons created as the final result of the photo-electric absorption.

While the voltage pulse in a "proportional counter" is only approximately proportional to the incident photon energy, the pulse is proportional to the number of electrons produced in the absorption region.

There are detailed predictions about the number of electrons produced by photo-electric absorption in Xenon (Dias et al. 1993). We define a second scale, E_p , proportional to the number of electrons produced and normalized to be approximately equal to energy.⁷

The average number of eV (w) required to produce one ionization electron in Xe is shown as a function of photon energy (E_{γ}) in figure 1 (Dias et al. 1993). The values of $w(E_{\gamma})$ are near 22 eV and we define

$$E_p = \frac{22.0}{w(E_\gamma)} E_\gamma. \tag{1}$$

With this definition there are discontinuities of 76.4, 10.9, and 12.6 eV in E_p at the Xenon L_1 , L_2 , and L_3 edges with $E_{\gamma} = 4.78, 5.10$, and 5.45 keV.

⁷The labels for the energy axis supplied by the PCA matrices are E_p .

We find that the PCA data are better fit with smaller jumps, and introduce a parameter f which lessens the difference between E_p and E_{γ} and reduces the size of the jumps. For values $0 \le f \le 1$ we define

$$w_f(E_\gamma) = (w(E_\gamma) - 22.0)f + 22.0.$$
 (2)

The value of the parameter f is optimized in our fitting procedure. Our best fit value for f is 0.4, resulting in a total jump of 40 eV summed across the three edges.

Our response matrix has an "instantaneous" quadratic relationship between channel and E_p . Within each high voltage epoch we fit a model where

$$ch(E,T) = A + BE_p + C_o E_p^2.$$
(3)

The constant and linear coefficients are time dependent:

$$A = A_0 + A_1 \Delta T + A_2 (\Delta T)^2 \tag{4}$$

and

$$B = B_0 + B_1 \Delta T + B_2 (\Delta T)^2 E_p.$$
 (5)

 ΔT is the time in days between T and a reference date T_0 . The cause of the time dependence is not known, but may reflect a slow change in purity or pressure of the gas or other changes within the amplifier chain.

3.2. Quantum Efficiency

The quantum efficiency of each PCU is modelled as a series of parallel slabs of material. No account is made of possible bowing of the front entrance aperture on any scale. All quantum efficiency parameters, specified in pcarmf.par and documented in table 3, are reported with units of gm cm⁻²:

We specify for each detector

- $Xe_{l(m)}$, the amount of Xenon in detector layer m; m runs from 1 to 3;
- Xe_{pr} , the amount of Xenon in the propane layer on 1997 Dec 20;
- Xe_{dl} , the thickness of a dead layer of Xenon between adjacent layers;
- Mylar, the total thickness of the two Mylar windows;

- $d(Xe_{pr})/dt$, the rate of change (per day) of Xenon in the propane layer;
- Aluminum The total amount of aluminization on the four sides of the two windows;
- Propane The amount of propane in the first gas volume

The dead layer, as modelled here, assumes that there is a small region where events will be self vetoed as part of the electron cloud is collected in one anode volume and part in the adjacent volume. In detail, such a region probably has a soft edge, though our data cannot distinguish this. Additionally, the model requires that PCU 0, despite the loss of pressure in the propane layer, requires residual Xenon in the propane layer in epoch 5. The best parameterization requires half as much Xenon as before the loss of pressure. This model is unsatisfactory, and the fits are less good for PCU 0 in epoch 5. There could be many causes, including bowing of the internal window which now supports a 1 atm pressure differential.

The Xenon absorption cross sections are from McMaster et al. (1969). all other absorption cross sections are derived from Henke et al. (1993).

Figure 2 shows the modelled quantum efficiency for PCU 2, layers 1, 2, 3 on January 13, 2002. The peak quantum efficiency decreases by $\sim 8\%$ over the first eight years of the mission due to the diffusion of Xenon into the front veto volume.

3.3. Redistribution matrix

Our model accounts for the intrinsic resolution of the proportional counter, K and L escape peaks, losses due to finite electron track length (which causes events to be self-vetoed), and losses due to partial charge collection (which causes events to show up in a low energy tail). These contributions are described in more detail below.

Proportional counter resolution is typically limited at high energies by fano factor statistics. At low energies there may be a significant component related to detector non-uniformities and readout electronics (Fraser 1989). The resolution ($\Delta E/E$, where ΔE is the FWHM) is ~ 0.17 at 6 keV and ~ 0.08 at 22 keV, measured with ground calibration sources. We model the resolution (FWHM) in channel space as

$$\Delta ch = (\sqrt{aE + b})B \tag{6}$$

where B is the slope term from equation 3.

The Xenon L-escape peak is not prominent. The 4.1 keV escape photon has a mean free path of 0.5 cm in 1 atm of Xenon. Escape is only possible from the first layer. For the inner

layers (and the front layer) there is a chance that the escape photon will be re-absorbed in an adjacent layer. The resulting coincident signals will affect the overall efficiency as the EDS will not recognize this as a good event. The model allows an efficiency correction for energies above the Xenon L-edges and below the K edge, though our parameterization sets this self vetoed fraction to 0. The overall normalization is adjusted by the values of geometric area which parameterize the tool xpcaarf.

Above the K-edge, only the K-escape peaks are modelled, and these are more prominent than the main photo-peak. Detailed prediction of the amplitudes would require a complex integration over the detector geometry, and might be slightly different for the three detector layers. We assume that the escape fraction is the same for each layer. Initial estimates of the escape fractions come from laboratory data obtained at the Brookhaven National Laboratory National Synchrotron Light Source ⁸ where small areas of one of the detector were illuminated by monochromatic beams. Our model allows a correction for self vetoing events when the escape photon is absorbed in a different anode volume. Our estimate of the non-self-vetoed fraction is 0.91. Among the remaining events, the majority (0.55 and 0.16 of the unvetoed events) appear in the K_{α} and K_{β} escape peaks while the remainder appear in the photopeak (see figure 3).

Events can be lost if the photo-electron travels into a second anode volume. Youngen et al. (1994) demonstrated the importance of this effect for the HEAO-1 A2 High Energy Detector (Rothschild et al. 1979) which has a similar internal geometry to the PCA. The Youngen model is a Monte Carlo, making it difficult to use the results directly. We model the unvetoed fraction as

$$f = 1.0 - A_o g(layer) \left(\frac{E_{electron}}{E_{point}}\right)^{\delta} \tag{7}$$

where $E_{electron}$ is the energy of the initial photo-electron, A_o is an amplitude, the factor g(layer) (= 1, 1.33, 1.33 for the first, second, and third layers) accounts for the fact that the inner detection cells have more edges which the electron might cross. Because the exponent δ is large (\sim 3), the fraction lost is near constant below E_{point} and rises quickly above this energy.

We also model partial charge collection. For X-rays which are absorbed near the edge of the active region, there is a competition between diffusion and drift towards the high field region where charge multiplication occurs. The effect has been modelled at low energies (Inoue et al. 1978) and parameterized in terms of the ratio $\kappa = \frac{D}{w\lambda}$ where D is the diffusion

⁸The Brookhaven National Laboratory National Synchrotron Light Source is supported by the U.S. Department of Energy. At the time of our visit, the Contract Number was DE-AC02-76CH00016.

coefficient, w is the drift velocity, and λ is the mean absorption depth. For an initial cloud of N_0 electrons, the number which reach the amplification region is

$$f(N)dN = \kappa (1 - \frac{N}{N_0})^{\kappa - 1} dN. \tag{8}$$

Jahoda and McCammon (1988) used this equation directly for an Argon based counter while Inoue et al. (1978) found it necessary to introduce an ad-hoc factor of ~ 3 for a Xenon based counter. We have chosen to treat the ratio of D and w as a free parameter which we fit. Strictly speaking, equation 8 applies only for energies where the photons are absorbed near the entrance window; however, this model predicts very small losses for energies where this condition is not satisfied, so we apply this model at all energies.

Figure 3 shows the redistribution function for lines with energies at 5, 9, and 50 keV to illustrate the magnitude of the incomplete charge collection, L-escape, and K-escape peaks. The normalization of the lines is arbitrary and selected for illustrative purposes.

3.4. Detailed construction of the matrix

This section describes the operation of the PCA response generator pcarmf; default values of the parameters and their mnemonics are listed in table 3 and described below.

The matrix is constructed to have 296 energy bins, spaced logarithmically from 1.5 to 80. keV. Extra bin boundaries are inserted at the three Xenon L edges and the Xenon K edge, so there are a total of 300 energy bins. The edge energies are read as the parameters xeL3edge, xeL2edge, xeL1edge and xeKedge. The matrix maps monochromatic input from the mean energy of each bin to 256 detector channels, indexed from 0 to 255 to match the channel-ids reported by the PCA to the EDS.

The response matrix generator works on one detector and one layer at a time. The detector is specified by *pcuid* with allowed values ranging from 0 to 4. The layer is specified by *lld* with allowed values of 3, 12, 48, 63, and 64 for the first, second, third, summed Xenon, and propane⁹ layers respectively. The date is specified by *cdate*, in yyyy-mm-dd format.

A matrix corresponding to the selected detector, layer, and date is generated with the following steps. For each energy in the matrix we

• Determine the overall quantum efficiency.

⁹The propane layer is poorly calibrated as we have no in flight energy scale diagnostics.

- Calculate E_p (equations 1 and 2); the parameter f is specified by w_xe_fact . ¹⁰
- Calculate the mean channel (ch_{mean}) . The coefficients in equation 3 are stored in pca_e2c_e05v03.fits found in the \$LHEA_DATA directory which is part of the FTOOLS v5.3 package. The latest version of this file is also available from the HEASARC calibration data base CALDB.
- Determine whether the photon energy is below the Xenon L3 edge (parameter x-eL3edge) where no escape peak is possible, between the L3 and K edge (parameter xeKedge) where an L-escape photon is possible, or above the K edge where both the Xe K_{α} and K_{β} escape photons are possible.
- For energies where escape peaks are possible, calculate the mean channel of the escape peak. The Monte Carlo and experimental results (Dias et al. 1996) indicate that $ch_{mean}(E_{esc}(E_{\gamma}))$ vs $E_{\gamma} E_{esc}$ is offset from $ch_{mean}(E_{\gamma})$ vs E_{γ} by up to 50 eV. The offsets are quantified in terms of a number of electrons; the offsets are parameterized as $delta_el_L$, $delta_el_Ka$ and $delta_el_Kb$ for the L, K_{α} , and K_{β} escape peaks respectively.
- For energies where K escape peaks are possible, the fraction of events in the escape peak are given by EscFracKa and EscFracKb for the K_{α} and K_{β} peaks respectively. The fractions are modelled to be the same for each layer in the detector. When K escape peaks are possible, the L escape fraction is modelled to be 0.
- For energies where the L escape peak is possible, the fraction of events in the escape peak is given by *EscFracLM* where *M* is 1, 2, or 3 corresponding to the layer that the photon is absorbed in. The default parameterization is no L escape peak for photons absorbed in the second or third layer, and 1% for photons absorbed in the first layer.
- For the main photo-peak, evaluate the resolution. The coefficients a and b in equation 6 are given by $resp1_N$ and $resp2_N$ where N identifies the PCU. These coefficients have not been separately fit by PCU.
- Correct the quantum efficiency for the effects of electron tracking (equation 7) where the coefficients A_o , E_{point} , and δ are given by $track_coeff$, epoint and $track_exp$.

¹⁰This is $e2c_model$ "3"; pcarmf is capable of handling an alternate energy to channel model (model "2") where $E_p = E_{\gamma} - \Sigma(\Delta_{edge})$. The Δ_{edge} are defined so that $E_p = E_{\gamma}$ between the Xenon L and K edges and E_p is greater (less) than E_{γ} for energies below the L edges (above the K edge). The size of the jumps, in keV, is given by $DeltaE_Ln$ and $DeltaE_K$ where n = 1,2,3. This model has a strictly linear E_p vs E_{γ} relationship between the edges. The energy to channel relationship has not been calibrated for this model.

- Distribute the corrected quantum efficiency, further corrected for the escape fractions, in a gaussian centered at ch_{mean} with and FWHM = 2.35 σ (equation 6).
- Treat the escape peaks similarly. The resolution and electron tracking are calculated for $E_{\gamma} E_{esc}$, and the resulting peaks are added to the 256 channel spectrum.
- Correct the entire 256 channel spectrum for partial charge collection (equation 8). As noted above, this is certainly unphysical for large energies, but the effect is small here, and the model is plausibly correct at the energies where the effect is important.

4. Calibrating the parameters

4.1. Energy Scale

Data suitable for calibrating the energy scale, and monitoring variations, comes from three regularly observed sources: the internal calibration source provides continuous calibration lines at 6 energies from 13 to 60 keV; approximately annual observations of Cas A provide a strong and well measured Iron line at 6.59 keV; and regular monitoring observations of the Crab nebula provide an opportunity to measure the location of the Xenon L-edge near 5 keV.

4.1.1. Calibration Source

Each PCU contains a small Am²⁴¹ source which provides a continuous source of tagged calibration lines with energies between 13 and 60 keV (Zhang et al. 1993). The energies and notes about each line are listed in table 4. Calibration spectra are telemetered with the full 256 channel resolution of the PCA, so we perform fits directly in channel space. A sum of 6 gaussians with a small constant and linear term provides an excellent fit. An example is shown in figure 4. The 60 keV line is well modelled by a Gaussian as the Compton cross section is beginning to become significant with respect to the photo-electric cross section. We have ignored this effect.

We collected calibration data from dedicated sky background pointings within each calender month of the mission (for the period before November 1996 when dedicated background observations began, we have used observations of faint sources). During months when the high voltage changed, we collected 2 distinct spectra. This procedure provides data which is systematics (i.e. not statistics) limited. For instance, the line near 26 keV is consistently

broader than the others as it is a blend of a nuclear line from the ${\rm Am^{241}}$ source and the K- α escape peak from the 60 keV line.

4.1.2. Cassiopeia A

The supernova remnant Cassiopeia A has a bright, strong, Iron line easily visible in the PCA count spectra. Cas-A has been observed approximately annually as a calibration source, and we have fit a model with a power law continuum and a gaussian line to the data between 4 and 9 keV (figure 5). Over this band pass, this simple model provides an acceptable fit to the data; over a broader band the models become quite complex (Allen et al. 1997). The fit energy centroid can be unambiguously converted to a mean channel. We assume that the actual average energy of the Fe line complex is 6.59 keV, consistent with *Ginga* (Hatsukade and Tsunemi 1992) and ASCA (Holt et al. 1994) results. The mean channel can be accurately determined without considering the line complex at 8.1 keV observed by Pravdo and Smith (1979) and Bleeker et al. (2001).

While there are relatively few pointings at Cas-A, and this line thus has limited weight in the channel to energy fits, it does provide a valuable check on the accuracy of the energy scale in the Fe line vicinity. Results are presented in section 4.4. While calibration near the Iron line is unavailable for the second and third Xenon layers, there is also little significant signal from cosmic sources here.

4.1.3. Xenon L-edge

Each detector has a front layer filled with propane; a small amount of Xenon is also present, due to diffusion either through the window or the o-ring seal that separates the two volumes. Although the presence of Xenon in this layer does reduce the efficiency in the active volume, it also provides a calibration opportunity. The regular monitoring of the Crab nebula plus pulsar allows us to measure and monitor the energy calibration near the Xenon L-edge at 4.78 keV.

A best fit matrix accounts for the Xenon in the propane layer, however we can construct a matrix which artificially sets the amount of Xenon to zero. The Crab continuum spectrum, analyzed with this incorrect matrix, requires an absorption edge to mimic the unaccounted for Xenon. Fits to this edge can be interpretted in terms of the energy scale.

We perform fits in energy space, and convert the fit energy back to channels. The resulting set of date/channel pairs for 4.78 keV are fed back into the procedure that determines

the energy to channel relationship. ¹¹

The Xenon L-"edge" has structure on a scale that is fine with respect to the energy resolution of the PCA. There are 3 edges with energies at 4.78, 5.10, and 5.45 keV. With proportional counter resolution these cannot be fit simultaneously. We use a model with a power-law, 3 edges, and "interstellar absorption" with variable elemental abundances; the absorption and edges mimic the absorption due to the Xenon in the propane layer. The energies of the second and third edges are fixed at 1.07 and 1.18 times the energy of the first edge, and the optical depth is fixed at 0.44 and 0.18 times the optical depth of the first edge (Henke et al. 1993). The absorption uses the XSPEC varabs model, itself based on the cross-sections tabulated by Balucinska-Church and McCammon (1992). We keep the relative abundances of H, He, C, N, O, and Al fixed with respect to each other. The abundance of Fe is allowed to vary. The abundances of all other elements are fixed at zero. This description is not intended to be physical, but rather to produce a fit with small residuals; examples are shown for PCU 2, layers 1 and 2, in figures 6 and 7.

The edges are quite precisely fit with typical 3σ errors less than ± 0.07 keV for the first layer. Systematics associated with the model are thus quite important. We have chosen the model described above because fits for the energy to channel relationship using this model provide self consistent results. We include over 100 observations in our determination of the energy to channel law, and the average is extremely well determined. We have chosen a parameterization for the edge model that provides good results (see section 4.4.3).

4.2. Energy to channel relationship

We fit the energy to channel relationship separately for each detector, layer, and epoch using a χ^2 minimization. The precision of the input data is highest at energies well above the PCA peak sensitivity. The errors on the calibration line channels, as a fraction of the channel, range from 10^{-3} for the lines at 13 and 21 keV to less than 5×10^{-4} for the lines at 17, 30 and 60 keV. The fractional errors on the L-edge channel and Cas-A line are $\sim 5 \times 10^{-3}$. The errors on the Cas-A line energy include a statistical component and are correlated with exposure time.

The mean photon energy observed by the PCA is always below 10 keV; to apply the maximum weight to the points nearest this mean, we reduce the error associated with the

 $^{^{11}}$ Fitting in energy space allows the use of the XSPEC convolution code as well as the pre-defined absorption models.

L-edge points points by a factor of 10. To apply approximately equal weight to each of the Cas-A points and remove the exposure dependence, we set all errors to 0.1 channel (about the mean). We are not using the chi-square minimization to estimate errors on the channel to energy parameters (equation 3) and we validate the results by examining the fits to the Crab nebula (section 4.4.3). This ad-hoc procedure for adjusting the errors is justified not by statistical rigor, but by reasonable results. Our fits are consistently poor for the line near 26 keV; we attribute this to poor knowledge of the mean energy of this blended line, and exclude it from our fits.

We produce energy to channel parameters for a range of values of the parameter f (eq. 2); selection of the best value of f comes after the process of adjusting the parameters associated with quantum efficiency and redistribution.

4.3. Quantum efficiency and redistribution

The response matrix contains many correlated parameters; we have used our frequent observations of the Crab nebula to make numerous estimates of the best values of the parameters, and then made a response matrix using averages over time, or over time and PCU.

For each observation of the Crab, we have collected the data and estimated the background separately for each layer of each detector. We use the channel to energy law to select data from each layer with $E_{min}(layer) \leq E_p \leq E_{max}(layer)$. For the first layer we use $E_{min} = 3$ keV and $E_{max} = 50$ keV; for the second and third layers we accept data from 8 to 50 keV.

These data are fit, via a chi-square minimization technique, to a model which parameterizes the response matrix and the Crab input spectrum. As parameters are highly correlated (i.e. the amount of Xenon in the first layer and the power law index for the Crab) we have adopted a procedure that minimizes a few parameters at a time, and revisits earlier steps as needed. The Crab photon index is fixed at -2.1.

Figure 8 shows the resulting fit values for the Xenon thicknesses of the first and second signal layers, the propane volume, and the dead layer for PCU 2. We require the Xenon thickness of the third layer to be equal to the second layer. The time scale is in days relative to 20 Dec 1997. Note that on this plot there is no discernable break in March 1999 (near day 500) when the high voltage was changed.

This procedure was repeated for several values of the parameter f. We selected the best

value of f by comparing the values of χ^2_{red} for power law fits to the Crab data in all three layers. By design all of these fits returned $\Gamma \approx 2.1$. Using χ^2_{red} as a discriminating statistic, there is smooth variation with f, as shown in fig 9. For almost all observations of the Crab with $0.35 \leq f_{min} \leq 0.45$, so we adopted f = 0.40 as the best fit value. The calibration of the Ginga Large Area Counters reports a total jump of 70 eV (equivalent to $f \approx 0.7$) summed across the three Xenon edges (Turner et al. 1989). The discrepancy in f, which represents the properties of Xenon rather than detector details, indicates that systematics remain in the Ginga and/or PCA models.

Table 3 gives the best fit values for the parameters. The parameters are more similar from detector to detector than for previous calibrations which were performed with a more ad-hoc approach.

4.4. Results

4.4.1. Effective Area

We adjusted the areas in xpcaarf so that we match the canonical Crab flux (Zombeck 1990; Toor and Seward 1974, 1977). Individual spectra from the Crab were corrected for both instrumental and source induced deadtime (typically $\sim 6\%$; see fig 26.) Following this, the area parameters in xpcaarf were adjusted so that the best fit flux matches the literature values. The net geometric areas were subjected to an upwards correction of $\sim 12\%$. This removes a substantial fraction of the discrepancy noted by, e.g., Kuulkers et al. (2003) and references therein, which was performed with a previous version of the response generator, which also systematically reported higher values of the photon index for the Crab.

Our procedure is to fit an absorbed power-law to the many observations of the Crab nebula. We use data from the first layer, and adjust the peak open area of the detector so that the average 2-10 keV flux is $2.4 \times 10^{-8} \, \mathrm{erg \, sec^{-1} \, cm^{-2}}$ (Zombeck 1990). The derived geometric areas, which are inputs to **xpcaarf**, are documented in table 3. For PCU 0 we use data only from epoch 3 and 4 as the epoch 5 calibration remains poor (see the step function in the best fit index in fig 11).

4.4.2. Energy scale

We re-fit the Cas-A line with our best fit matrix and plot the results in fig 10. The fits return a narrow line. The centroid position is fit only to ~ 0.15 keV due to a combination

of the intrinsic resolution of the detector and the steepness of the underlying continuum ($\Gamma \approx 3$). These errors are representative of the accuracy that can be expected from fits to strong lines.

4.4.3. Spectrum of the Crab Nebula

The Crab offers three checks on the quality of the response matrix. First, it allows us to establish consistency with previous results since the integrated emission is believed to be time stationary. Second, it allows us to establish whether our matrix properly accounts for the time dependencies in the detectors, and provides the same results over the nearly nine years (and counting) lifetime of the mission. Third, we can examine the residuals to the fits and thus estimate how large residuals in fits to other sources must be before simple continuum models are deemed inadequate.

The first two points are addressed in figures 11 through 15 which present the best fit power-law index for about one-quarter of the Crab monitoring observations using the matrix generator in the FTOOLS v5.3 release (crosses), as well as the previous calibration (open squares). The lower panel in each figure shows the reduced χ^2 associated with the two versions. By construction, the best fit power-law index is now more consistent from PCU to PCU (particularly at late times where the previous calibration provided an estimate based on extrapolation). These figures show fits to layer 1 only, which provides the large majority of the detected photons and the largest bandwidth. That the reduced χ^2 is typically greater than 1 indicates that unmodelled systematics remain.

The data and model, along with the ratio of data to model, fit to a representative Crab monitoring observation are demonstrated in figures 16 and 19. The data are from 1999-02-24 and the best fit power law indices are 2.08858, 2.09877, 2.10551, 2.08780, and 2.09570. The deviations from the power law are quite similar from one detector to the next. Figure 17 shows an enlargement of the 3-20 keV region; below 10 keV the deviations are less than 1%. Between 10 and 20 keV the data begins to exceed the model slightly, though only by $\sim 2\%$. There is a clear underprediction just below the Xenon K edge; although this is quite obvious in the ratio presentation, the number of counts per channel (the convolution of the intrinsic spectrum with the detector quantum efficiency, both of which decline rapidly with energy) is nearly three orders of magnitude below the peak. Figure 18 shows the contributions to χ^2 , which are dominated by deviations at the lowest energies and near the Xenon L edge, where the counting rates are high.

Figure 19 shows fits to data from all three layers. The data are from 2003-02-26, PCU 2;

the power law indices are constrained to be the same (best fit 2.12297) The normalizations are allowed to float; the variation (max to min) is less than 3%. Requiring the normalizations to be the same does not change the best fit index.

5. Background model Overview

The RXTE PCA is a non-imaging instrument; for both spectroscopy and light curve analysis the background must be subtracted based on an a priori model. "Background" is defined broadly to include anything that contributes non-source counts to the PCA instrument in orbit, including but not limited to:

- local particle environment;
- induced radioactivity of the spacecraft; and
- the cosmic X-ray background.

In general, these components vary as a function of time, and must be parameterized. The parameterized model is adjusted to fit a set of dedicated observations by the PCA of blank sky regions. Once a good fit is achieved, the same parameterization can be applied to other observations.

Figure 20 shows the spectra of the "good" count rate during observations of blank sky; this is the total (i.e. instrument plus sky) background. Spectra are shown separately for the first, second, and third layers. The peaks near channels 26 and 30 keV are due to unflagged events from the Am²⁴¹ calibration source. The fractional contribution of sky background to each layer is shown in the lower panel. The sky background is approximately 1 mCrab per beam. The lower light curve in figure 21 shows the total background rate over a two day period of nearly uninterrupted observations of blank sky. Variations by more than a factor of 2 in a day, and by up to a factor of 1.5 in an orbit are clearly visible.

The most successful background model to date for faint sources is the "L7/240" model. Here, "L7" is the name of a housekeeping rate which is well correlated with most of the variation in the PCA background rate. The L7 rate is the sum of all pairwise and adjacent coincidence rates in each PCU. The "240" component refers to a radiactive decay timescale of approximately 240 minutes. This timescale may describe the combined effect of several radioactive elements. The L7/240 model is not appropriate for bright sources because the L7 rate can be modified by the source itself.

The "Very Large Event" housekeeping rate is also correlated with the observed background rate, although with more unmodelled residuals than the L7 rate. Both the L7 and VLE rates are shown in figure 21. Gaps in the blank sky and L7 rates exist due to observations of other sources while the VLE rate is shown throughout, and is virtually unaffected by even bright X-ray sources. Since the VLE rate is largely unaffected by the source rate, makes it can parameterize a model suitable for "bright" sources. Operationally, bright is defined to be 40 source counts per sec per PCU or about 15 mCrab.

The background model is determined by fitting high latitude blank sky observations which are regularly obtained in 6 directions. The output of the background model is an estimate of the combined spectrum of instrument background and the Cosmic X-ray Background observed at high latitudes. The model makes no attempt to predict the diffuse emission associated with the galaxy (Valinia and Marshall 1998).

When background observations were begun in November 1996, one day was devoted to this project every three or four weeks. Eventually this was supplemented by short, twice daily observations to better sample the variations that are correlated with the apogee precession of ~ 30 days. Because the orbit apogee and perigee differ by about 20 km and because the particle flux within the South Atlantic Anomaly varies with altitude, the average daily particle fluence, and the radioactive decay component of the background, show a long term variation with this period as well.

The blank sky observations were originally divided among 5 distinct pointing directions. Daily observations of a sixth point were added in order to test the success of the background modelling for the lengthy NGC 3516 monitoring campaign (Edelson and Nandra 1999). The pointings are summarized in table 5.

The current background models 12 have explicitly linear dependences on L7 (or VLE), the radioactive decay term, and mission elapsed time.

In the construction of these models, we

- accounted for the variance in L7 (or VLE) itself;
- derived coefficients for each Standard2 pulse height channel independently;
- used a modified chi-square approach for low-statistics Poissonian data (Mighell 1999)

¹²http://heasarc.gsfc.nasa.gov/docs/xte/pca_news.html#quick_table provides links to the current models, and details of the special requirements and limitations of the model for PCU 0 after the loss of the propane layer.

- included data from immediately after the SAA (i.e. included more data than in earlier efforts)
- selected data with a horizon angle of at least 10 deg and with the rates VPX1L and VPX1R (contained within the Standard2 data) less than 100 sec⁻¹

The fitted background model for each channel, i, is:

$$BKG_i = A_i + B_i * L7 + C_i * DOSE + D_i * (t - t0)$$
(9)

where A_i , B_i , C_i and D_i are the fit coefficients, L7 is the L7 rate in a PCU, DOSE is the SAA particle dosage summed over individual passages through the SAA and decayed by a 240 minute folding timescale, and t is the epoch time. The SAA particle dosage is measured by the particle monitor on the High Energy X-ray Timing Experiment (Rothschild et al. 1998) also aboard the RXTE; each passage is defined as the period when the HEXTE high voltage is reduced. Equation 9 is linear in all its terms, and allows for a secular drift over time. The secular drift in time has been ~ 0.07 ct s⁻¹ PCU⁻¹ yr⁻¹ from epoch 3B through the present, and is well correlated with satellite altitude. This term became significant when the RXTE orbit began to decay. We parameterize the time dependent term as a linear trend within each epoch; there is a discontinuity in the slope at epoch boundaries, with the significant discontinuity at the beginning of epoch 3B corellated with the time when the satellite orbit began to decay noticeably (fig 22). The orbit decay is understood to be due to increased drag as the earth's atmosphere expanded in response to increased solar activity associated with the solar cycle. The satellite altitude has changed from 580 km at the beginning of epoch 3B to ~ 500 km in fall 2003.

VLE models require a second activation time scale; the second DOSE term is decayed by a 24 minute time scale. Attempts to fit the time scales are poorly constrained, probably due to the fact that both timescales are a mixture of several radioactive half-lives; additionally, for the shorter timescale the DOSE term, which sums the fluence of particles on orbital timescales, may not contain enough time resolution. The quality of the resulting background spectra has been high enough that a more careful parameterization has not been needed, and we have not succeeded in identifying particular radioactive decays that are responsible. All of the identified variations were also observed by the Large Area Counters on *Ginga*, although with different amplitudes related to the details of the orbit and detector construction (Turner et al. 1989; Hayashida et al. 1989)

Figures 23 and 24 show the coefficients B_i and C_i for PCU 2, layer 1, during epoch 5 and show that the background varies in both amplitude and spectrum.

The fitting was applied to multiple, dedicated, PCA background pointings. Each of the points on the sky has a slightly different sky background. Our approach is to assign a different set of coefficients A_i for each background pointing. The production background model is determined by taking the weighted average of A_i 's for different pointings. Thus, the background model represents an "average" patch of high latitude sky.

Remaining count-rate variations after background subtraction are a measure of systematic error. Figure 25 gives the systematic error per channel while Table 6 gives some band averaged values for individual layers of each detector. In each case we report the unmodelled variation in ct s⁻¹ PCU⁻¹ and as a fraction of the average background. These calculations were done by measuring differences between predicted and measured blank sky counting rates on 1600 sec timescales; on shorter timescales the variations are dominated by statistical error.

6. Timing Calibration

Every event detected within the PCA, whether a cosmic X-ray or an instrument background event, produces 19 bits which are passed to the EDS which adds the time stamp and performs event selection and rebinning.

Each signal chain has its own analog electronics chain consisting of Charge Sensitive Amplifier, Shaping Amplifier, Discriminator, and Peak Finder. The deadtime associated with the analog chains is paralyzable. The six Xenon signal chains and the Propane signal chain share a single Analog to Digital Converter which produces a 256 bit pulse height; the Xenon veto chain is separately analyzed and produces a 2 bit pulse height. The Analog to Digital Conversion is non-paralyzable. "Good" events produce charge on a single chain; the resulting pulse height can be unambiguously identified with that chain. For events which produce more than one analog signal, the pulse height cannot be unambiguously assigned to a particular chain; such events are generally not included in the telemetry except to be counted in the rates present in the Standard data modes.

6.1. Deadtime

A detailed description of the effects of deadtime on a particular observation depends on both the source brightness and spectrum. The spectrum affects the ratio of events observed in the first layer and other layers, and therefore changes the details of the interaction of a paralyzable deadtime process (associated with each analog chain) and a non paralyzable process (the analog to digital conversion). Fortunately, a complete description is not required for the most needed corrections. We present useful approximations for a common statistical representation of the data (power spectra) and for the construction of light curves.

6.1.1. Power Spectra

Even at relatively low count rates, the probability that events are missed has a significant effect on the shape of the power spectrum (Zhang et al. 1995).

A period of deadtime can be generated by one of the following:

- (1) An X-ray event: An X-ray event causes the detector to be dead in two ways. First, it disables its own analog electronic chain, i.e., the Charge Sensitive Amplifier (CSA), Shaping Amplifier (SA), and the associated discriminators for a period of time which depends on the amount of energy it has deposited in the detector; this is a paralyzable dead time. Each detector has 7 analog electronics chains (6 Xenon half-layers and the propane layer) which share an Analog to Digital Converter (ADC). Second, this event causes the entire analog chain to be busy for $10.0\mu s$; this is a non-paralyzable dead time which consists of $6.5\mu s$ of analog to digital conversion time plus fixed delays to allow the analog signal to settle (prior to the conversion) and for the data to be latched for transfer to the EDS and reset (after the conversion). For events with energy less than $\approx 20 \text{ keV}$, the analog chain is again live before the end of the ADC conversion. The minimum time between sequential events on the same or different chains is $10\mu s$, and to a good approximation, all events can be considered to have this deadtime.
- (2) A background event: a background event can be either a charged particle or an X-ray and causes the detector to be dead in exactly the same way as an X-ray if it occurs on one of the signal chains. If the event produces a signal on two or more anode chains, each of the anode chains is paralyzably dead, and one of the signals is presented to the ADC (no information is available on which signal). The ADC is busy as above. If the event occurs on one of the background chains, V_x or Alpha, it vetoes the detector for a non-paralyzable $6\mu s$ though the possibility exists that the V_x or Alpha chain will be unavailable for longer. The detector is effectively dead during the $6\mu s$ because any event occurring, during this time is, by definition, rejected.
- (3) A Very Large Event (VLE): a VLE is operationally defined as an event which exceeds the dynamic range of the experiment and saturates the amplifier. The equivalent energy depends on the high voltage setting, and was ~ 75 keV in Epoch 1 and ~ 120 keV in Epoch 5. The default VLE window is $170\mu s$ (Zhang et al. 1996). See also section 2.1.

The Poisson random noise level is suppressed by the correlation between events caused by the deadtime. To a good approximation, the Poisson noise level with deadtime correction can be computed as follows:

$$P_d(f) = P_1 - P_2 cos(\frac{\pi f}{f_{Nyq}}) \tag{10}$$

 P_1 and P_2 depend in principle on the details of the electronics. For count rates less than 10^4 ct s⁻¹ PCU⁻¹ (or ~ 4 Crab) the dependence is small and both coefficients can be estimated as if the deadtime is purely paralyzable with

$$P_1 = 2[1 - 2r_0t_d(1 - \frac{t_d}{2t_h})]$$
and (11)

$$P_2 = 2r_0 t_d \frac{N-1}{N} (\frac{t_d}{t_b})$$
 (12)

where r_0 is the output event rate, t_b the bin size, t_d the deadtime taken to be 10μ s, N is the number of frequencies in the power spectrum, and f_{Nyq} is the Nyquist frequency (Zhang et al 1995). The dead time in P_1 and P_2 is calculated as 10μ s times the total number of (non VLE) events transferred to the EDS per detector plus 170μ s times the number of VLE events per detector. These rates can be estimated from the Standard 1 rates assuming that the summed rates come equally from all detectors which are on.

We need to include the contribution to the power spectrum by the VLE events. Since VLE events cause "anti-shots" in the data, its contribution can be written as

$$P_{vle}(f) = 2r_{vle}r_0\tau^2(\frac{\sin \pi \tau f}{\pi \tau f})^2, \tag{13}$$

where r_{vle} is the VLE rate, r_0 the good event rate, and τ the VLE window size (Zhang et al. 1996). In practice one needs to add up equations 10 and 13.

6.1.2. Light Curves

Faint Sources For the purposes of this discussion, a faint source is one where the deadtime correction is less than 10%. This includes the Crab. Dead time is produced by all events within the detector, and can be estimated from either Standard1 or Standard2 data as both modes count each event presented to the EDS once. We illustrate this with observations of the Crab.

Figure 26 shows the total good rate (sum of the 5 rates from the individual detectors) and the deadtime corrected rate in the top panel; the calculated deadtime is shown in the lower panel, along with the contributions to deadtime from instrumental background rates. The deadtime is calculated from the total rates, including the good rate (the observed rate in the top panel) and the rate of VLE, Propane, and "Remaining" events collected in the Standard 1 data. Each event contributes $10\mu s$ to the deadtime except for Very Large Events which contribute 170μ s. We use the Standard 1 rates; for the rates which are summed over all PCU, we assume that the contribution from each PCU is the same. 13 Estimating the incident rate with this proceedure is adequate in practice although it ignores one detail of the PCA electronics. Some of the events included in the Standard 1 "Remaining" rate trigger only the Xenon Veto anode (i.e. and not any of the signal anodes) and are handled differently than the other events. These events do not initiate an analog to digital conversion and the 8 pulse height bits transferred to the EDS are therefore set to 0 as are the lower level discriminator bits. While there is a dead period where no good event can be recorded due to the presence of the veto signal, it is known that no incident event was lost in these dead periods. (If there had been an event, the analog to digital conversion would have been initiated, and a multiple anode - i.e. rejectable - event would be transferred to the EDS.) The dead time correction accounts for periods where an incident event would go un-noticed. Since the VX only events do not prevent us from noticing incident events, they should not be included in the sum of "dead time". In practice this is a small effect which can be estimated on 16 second time scales from the Standard 2 data which records the total rate of VLE (only) events. For the interval shown in fig 26 about two-thirds of the instrument background induced deadtime is due to Very Large Events. The Vx only rate is $\sim 14\%$ of the rate of all other multiples events. The dead time relevant for estimating the incident rate is therefore over estimated by ~ 0.0014 of the total live time.

The total observed rate is modulated by occulted periods, and is $\sim 13,000$ count sec⁻¹ when on source. The remaining count rate is modulated at twice the orbital period (and is correlated with earth latitude, McIlwain L, or rigidity); in addition there is a contribution to the remaining count rate due to the source itself. This represents chance 2-fold coincidences of X-rays from the Crab. For the Crab, peak deadtime from all sources amounts to $\leq 7\%$.

Deadtime corrections similar to this example will need to be performed for all observations attempting to measure relative flux variations to better than a few per cent. The time scales for background induced variation are about 45 minutes (half an orbit) although

¹³This assumption becomes less true in Epoch 5, when PCU 0 is no longer functionally identical to the others. A more careful analysis could estimate the instrumental contributions from Standard 2, which has sufficient time resolution to capture variations in the instrument background induced deadtime

source variability can cause variations in the deadtime on much faster time scales.

Bright Sources We operationally define bright sources as those sources for which it is inappropriate to treat all incident events as independent. The definition is therefore dependent on how the data is used. For instance, for power spectrum analysis, deadtime must always be considered, as the chance that events are miscounted or missed altogether changes the shape of the power spectrum. For the construction of light curves, on the other hand, the faint correction described above works well for sources with net counting rates $\leq 10,000$ count \sec^{-1} per PCU. At higher count rates it is important to correct for the chance that two cosmic photons are simultaneously detected in different layers (Jahoda et al. 1999) or in the same layer (Tomsick and Kaaret 1998).

7. Absolute Timing

Accuracy of the RXTE absolute timing capability on scales longer than 1 second has been verified by comparison of burst arrival times with BATSE. We have used both bursts from J1744-28 and a bright gamma-ray burst (960924) which produced a large coincidence signal in the PCA to establish this agreement. All information on times finer than 1 second is contained within individual EDS partitions. The relationship between EDS partitions and spacecraft time has been verified through ground testing and correlation of time tagged muon data with PCA data containing signals from the same muons. The content of the RXTE telemetry, and the relation to absolute time, has been thoroughly documented by Rots et al. (1998) and references therein. The telemetry times in the RXTE mission data base give times that are accurate to $\leq 100\mu$ s and users who require times $\leq 10\mu$ s can achieve this by applying correction terms¹⁴ which are measured several times a day by RXTE mission operations personel.

The phase of the primary peak of PSR 1821-24 has been measured in 30 different satellite orbits over the course of 3 days (Saito et al. 2001). The statistical accuracy of each measurement is ~ 0.003 in phase ($\sim 10\mu$ s) which is virtually identical to the distribution of measured phases. We can therefore conclude that the stability of the clock is better than 10μ s over 3 days. The scatter in the phases includes variation from clock variability, pulsar timing noise, and statistical uncertainty. The shape of the pulse is quite narrow (Rots et al. 1998).

¹⁴http://heasarc.gsfc.nasa.gov/docs/xte/time_news.html

7.1. Error Budget

In this section we examine the potential contributions to the uncertainty in computing the photon arrival times at the solar system barycenter. We consider the effects attributable to the detector and spacecraft, to the ground system, and to the barycentering computation. The effects are tabulated in table 7 and discussed below.

X-ray photons enter the Xenon volume of the PCA where they interact and are converted to photoelectrons, and subsequently to an ionization cloud which drifts to the anode wires where an electron avalanche is created. The drift time is approximately $\sigma_{\text{drift}} = 1\mu\text{s}$. Once collected at the anode wires, the electron pulse is amplified, shaped and converted to a digital pulse height. This conversion process takes approximately 18.2 μ s for all PCUs, and is essentially independent of energy.¹⁵

When an X-ray event is registered in the PCA electronics, its pulse height is transferred to the EDS over a 4 MHz serial link, where a time stamp is applied. The resolution of the RXTE clock is $\sigma_{\rm EDS} = 1\mu s$. In GoodXenon event mode, the full time precision of each event is kept. For other event modes with coarser time resolution, $\sigma_{\rm evt}$, the event time is rounded down (i.e., truncated), so on average an event will appear "early" by a time $\sigma_{\rm evt}/2$.

The RXTE clock, which is used to time-tag each X-ray event, is calibrated using the User Spacecraft Clock Calibration System (USCCS) (Rots et al. 1998). In short, the White Sands Complex sends a clock calibration signal via TDRSS to the spacecraft. The spacecraft immediately returns the signal to White Sands via TDRSS. Both send and receive times from White Sands are recorded with 1μ s precision for each calibration, and typically 50–150 calibrations are performed per day. When the calibration signal is received by the spacecraft, it also records the value of its clock. When the spacecraft and White Sands time tags are later processed on the ground in the RXTE Mission Operations Center (MOC), it is possible to determine the time difference between the spacecraft clock and the White Sands cesium atomic clock. The effective frequency of the spacecraft clock is routinely adjusted to keep time differences within $\pm 70\mu$ s of the White Sands clock.

The USCCS calibration signals are embedded in the spacecraft ranging measurements. Individual signals are sent at intervals much shorter than the light travel time to the spacecraft, so some information on the orbit ephemeris is needed to pair up the downlink time stamps with the correct uplink time stamps. The spacecraft ephemeris is estimated by the

¹⁵As discussed by Rots et al. (1998), the time for the lower level discriminator threshold to be met is energy dependent, but the analog to digital process does not occur until the pulse *peak* is reached. Thus, the conversion time is largely energy independent.

Goddard Flight Dynamics Facility (FDF), using spacecraft ranging data obtained through the TDRSS link. The FDF produces daily "production" solutions with approximately 8 hours of overlap with the previous day. We have performed a comparison of the overlap regions between daily solutions in order to provide an estimate of the ephemeris uncertainty. Over the mission lifetime, the overlap differences are less than ~ 450 m with 99% confidence, or $< 1.5\mu s$ light travel time. However, before the increase in solar activity starting around the year 2000, the uncertainty was approximately a factor of ten smaller than this.

The White Sands clock is formally required to keep station time within $\sigma_{\rm WS}=5\mu{\rm s}$ of UTC, as defined by the US Naval Observatory master clock, but is also required to maintain knowledge of this time difference at the $\pm 0.1\mu{\rm s}$ level. In practice, over the time period 1996–2001, this difference has been kept to within $\sigma_{\rm WS}=1\mu{\rm s}$ of UTC(USNO). Station time is actually compared against Global Positioning Satellite (GPS) time. GPS time, in turn, is kept within $\sigma_{\rm GPS}=100$ ns of TT(BIPM), the international standard of ephemeris time, according to published values in BIPM Circular T from 1996 to 2001.

The clock offsets derived from USCCS can be used to correct X-ray event times to White Sands station time. A piecewise continuous quadratic function is fitted to segments of clock calibration offsets. This function serves both to interpolate between gaps, but also to smooth individual calibration points. The function is constrained at each endpoint to be continuous in value with surrounding segments. In addition, discontinuities in slope are known because spacecraft clock frequency adjustments occur at known times and with known magnitudes. The granularity of clock frequency adjustments is 1/3072 Hz. Thus, the actual function is highly constrained, which is appropriate since we believe the clock to be largely well behaved. The clock model we have constructed matches the data to within $\sigma_{\rm model} = 2.5 \mu \rm s$.

Before MJD 50,567 a software processing error in the MOC caused individual clock calibration times to jitter at a level of $\pm 8\mu$ s. While the fitted quadratic model serves to smooth this jitter significantly, the variance in model residuals is significantly larger before MJD 50,567. We estimate that 99% of the residuals lie within $\sigma_{\text{MOC}} = 4.4\mu$ s of zero. After that date, the variance of the calibration points is contained within the band defined by σ_{model} .

Assuming the effects in table 7 are uncorrelated, which we expect to be the case, the total error will add the terms in quadrature. Thus, the absolute timing error for most of the mission is $< 3.4\mu s$ (99%).

8. Field of View

8.1. Collimator model

Each PCU has a collimated, approximately circular, field of view of radius 1° from peak to zero throughput. Each PCU has a collimator assembly made up of 5 individual collimator modules. Each module contains a large number of identical hexagonal tubes which provide the collimation and each module was aligned independently. The opening of each individual hexagon is 0.125 inch (flat to flat); the length of each collimator tube is 8 inches.

To model the on-orbit collimator efficiency we began with the theoretical transmission function for a perfectly absorbing hexagonal tube with dimensions equal to those comprising the PCA collimator modules. The fabrication, mounting and alignment of the collimator modules must introduce some level of misalignment among all the individual hexagons making up the collimator assembly. To produce a more realistic model we averaged the responses from a large number of perfect hexagons but with the pointing direction of each tube randomly displaced from the vertical. The random offsets were parameterized with a single parameter, σ , which represents the width, in arcmin, of a gaussian distribution centered on the vertical from which the random offsets were sampled. Thus, the larger σ the greater is the spread in pointing directions of the individual hexagonal tubes. We calculate the model response by randomly drawing an off axis angle, θ , from a gaussian distribution centered on $\theta = 0$ and with a standard deviation σ . A random value for the azimuthal angle ϕ is also selected. The theoretical transmission for this orientation is calculated and added to the total. The process is repeated for a large number of offsets, and the final total response is normalized to 1.0 at its peak. We calculated a series of models for different values of σ , ranging from 1 arcmin to 8 arcmin, and conclude that $\sigma = 6$ arcmin provides the best description of the collimators.

We used the Crab as an approximately constant and point-like source of X-rays in order to determine the boresight direction for each PCU as well as the value of σ which gave the best fit to the scan data. The RXTE spacecraft attitude control system (ACS) computes an estimate of the spacecraft attitude on a 0.25 second timescale. The attitude information prescribes the orientation of the three spacecraft axes in Earth-centered inertial coordinates (epoch J2000). The attitude data is provided by two on-board star trackers, and includes on board aberration correction. With this knowledge the location of any X-ray source with respect to the spacecraft coordinates can be calculated. We used the attitudes to determine the counting rate in each PCU from the Crab as a function of position in the spacecraft

frame. We then minimized the function

$$\chi_j^2 = \sum_i \frac{\left(O^j(Y_S^i, Z_S^i) - R^j M(Y_S^i - Y_{bore}^j, Z_S^i - Z_{bore}^j, \sigma)\right)^2}{O^j(Y_S^i, Z_S^i)} , \tag{14}$$

where O is the observed countrate, M is the model response, i denotes the individual rate and attitude samples, j denotes the different PCUs, Y_{bore}^{j} and Z_{bore}^{j} specify the pointing direction (boresight) of each detector, σ specifies the smearing of the ideal hexagonal response discussed above, and R^{j} denotes the peak countrate for each detector, that is the counting rate at the peak of the response. Since sources are effectively at infinity only the direction is relevant. The direction to the source with respect to the spacecraft frame can be uniquely specified with only two parameters. We elected to use the Y_{S} and Z_{S} spacecraft coordinates as the independent variables. Since these form part of a unit vector we have that $X_{S}^{2}+Y_{S}^{2}+Z_{S}^{2}=1$. Before performing the fit we first corrected the observed rates for detector deadtime using the faint deadtime correction formula described above. We found that $\sigma=5-6$ arcmin gave the smallest values of χ^{2} . Table 9 summarizes the derived values of Y_{bore}^{j} and Z_{bore}^{j} as well as the definition of the spacecraft "science axis". It is the science axis which the ACS points towards a commanded position.

8.2. Fidelity of the Collimator Model

In order to assess the accuracy of the collimator model we have carried out comparisons of the observed (background subtracted and deadtime corrected) and predicted counting rate from the Crab along various scan trajectories across the collimators. Results from a characteristic scan are summarized in Figures 27 to 29. Figure 27 shows the collimator efficiency model (as a contour plot) for PCU 0; the vertical line represents the scan trajectory of figures 28 and 29. Figure 28 shows the counting rate in PCU 0 along this scan trajectory (histogram with error bars) as well as the predicted countrate from the PCU 0 collimator model (solid curve). The observed rate tracks the predicted rate rather closely. Finally, to better quantify the fidelity we show in Figure 29 the ratio of (Data - Model)/Model along the scan path. The collimator model is faithful to the data at the few percent level on this scan, which is typical of all 5 PCUs.

8.2.1. Position accuracy using the collimator model

An important capability of RXTE is its ability to respond quickly to changes in the X-ray sky, for example, to observe the appearance of a new X-ray source. A crucial aspect

of such observations is the ability to rapidly localize the source so that observations in other wavebands can be attempted. Sky positions can be determined from observations in which the PCA is scanned over the source of interest. The observed lightcurve is compared to a model lightcurve derived from the spacecraft attitude data, the collimator models, and a source model which includes the celestial coordinates. The source model parameters are varied in order to minimize some goodness of fit quantity (typically a χ^2 statistic). The collimator models are an important component of this fitting procedure. Other factors which affect the precision of position determinations are a statistical uncertainty related to the brightness of the source, a systematic uncertainty introduced by intrinsic source brightness variations, nearby and unmodelled sources, and errors in the spacecraft attitude determination. Of these the most difficult to quantify for any particular object is the systematic error due to source variability. Nevertheless, this suggests another way to probe the quality of the collimator models by comparing the positions of known sources to those determined from scanning observations with the PCA.

Over its ~ 9 yr mission RXTE has performed scanning observations of many X-ray sources, and many of these either had or now have positions accurate at the arc-second level. We analyzed a sample of 13 bright sources and compared their known positions with those derived from PCA scanning observations. The results are summarized in Figure 30, which shows the offsets between the known and PCA-derived positions. For each source the offset is represented as a vector in the spacecraft coordinate frame. The length of the vector represents the angular separation between the known and fitted position. The thick portion of each vector is an estimate of the statistical uncertainty in the derived position. Thus, the thin portion provides an indication of the scale of the systematic error due to source variability and other effects. The dotted circle has a 1/2 arc-minute radius. Most sources are localized to better than 1 arc-minute, however, for a significant number of objects with small statistical errors the systematic error dominates.

Since the component of error due to source variability should be approximately random, one should be able to reduce it by averaging position determinations from many independent scanning observations. A bright source which is nearly ideal for such a study is the LMXB 4U 1820–30. This object resides in the Galactic bulge and has been observed hundreds of times during the course of PCA Galactic Bulge monitoring (Swank and Markwardt 2001; Markwardt et al. 2002) and its position is known to sub-arcsecond accuracy (Sosin and King 1995). We determined positions using many such observations of 4U 1820–30 and for each PCU separately. The results are summarized in Table 10. For each detector we give the number of observations analyzed, the average derived right ascension, α , and declination, δ , (both J2000), the angular separation, $\Delta\theta$, from the known position, and an estimate of the statistical error of the angular separation, $\Delta\theta$, these results suggest that in the absence

of source variability errors the position accuracy achievable with the PCA collimator model is in the 2–10 arcsecond range. This is becoming comparable to the pointing accuracy of RXTE. We note that the results from PCUs 0–4 are all more or less consistent.

8.3. Solid Angle

The linear approximation for the response, $f = 1 - r/r_0$ where r_0 is equal to 1 deg, overestimates the solid angle. Numerically integrating $f(r)sin(r)d\Omega$ over $0 \le \theta \le 2\pi$ and $0 \le r \le r_0$ gives 0.000320578 sr.

Integrating the summed responses numerically for all the PCUs, using the model file pcacoll_v100.2, we get 0.00029703 sr, or about 8% less. This is approximately the effective solid angle of a linearly falling response out to r_0 if $r_0 = 0.965$ deg. Put another way, this is the solid angle you get by integrating a flat (unit) response from r = 0 to 0.55712 degrees.

9. Summary

The PCA is a large and versatile instrument with well understood and systematics limited calibration. PCA observers command only the data compression; the appendix describes how the effects of data compression can be exactly modelled. The accuracy of the energy response function is limited by systematics below the Xe K edge; deviations from power-law fits to the Crab Nebula plus pulsar are less than 1% below 10 keV and gradually increase towards higher energies. Unmodelled variations in the instrument background are less than 2% of the total sky plus instrument background below 10 keV and less than 1% between 10 and 20 keV. The PCA has a dynamic range of 4.5 orders of magnitude: it is confusion limited at fluxes below $\sim 4 \times 10^{-12} \, \mathrm{erg \, sec^{-1} \, cm^{-2}}$ and deadtime limited at count rates greater than 20,000 ct $\mathrm{sec^{-1} \, PCU^{-1}}$ ($\sim 2 \times 10^{-7} \, \mathrm{erg \, sec^{-1} \, cm^{-2}}$ for a Crab like spectrum).

The RXTE mission is made possible by the support of the Office of Space Sciences at NASA Headquarters and by the hard and capable work of scores of scientists, engineers, technicians, machinists, data analysts, budget analysts, managers, administrative staff, and reviewers.

Facilities: RXTE(PCA), HEASARC

REFERENCES

- Allen, G. et al. 1997, ApJ, 487, L97.
- Arnaud, K.A. 1996, in ASP Conf. Ser., Vol. 101, Astronomical Data Analysis Software and Systems V, ed. G. Jacoby and J. Barnes (San Francisco: ASP), 17.
- Balucinska-Church, M. and McCammon, D. 1992, ApJ, 400, 699.
- Bavdaz, M., Martin, D., and Peacock, A. 1995, Proc. SPIE 2518, 465.
- Blackburn, J. K. 1995, in ASP Conf. Ser., Vol. 77, Astronomical Data Analysis Software and Systems IV, ed. R. A. Shaw, H. E. Payne, and J. J. E. Hayes (San Francisco: ASP), 367.
- Bleeker, J. A. M., Willingale, R., van der Heyden, K., Dennerl, K., Kaastra, J. S., Aschenbach, B., and Vink, J. 2001, A&A, 365, L225.
- Dias, T.H.V.T, Santos, F.P., Stauffer, A.D., and Conde, C.A.N. 1993, Phys. Rev. A, 48(4), 2887
- Dias, T.H.V.T, Santos, F.P., Santos, J.M.F., Lopes, J.A.M., Veloso, J.F.C.A., Rachinhas, P.J.B.M., Morgado, R.E., Stauffer, A.D., and Conde, C.A.N. 1996, IEEE-NS43, 1432.
- Edelson, R. and Nandra, K. 1999, ApJ, 514, 682.
- Fraser, G.W., "X-ray Detectors in Astronomy", 1989, (Cambridge University Press:Cambridge)
- Glasser, C. A., Odell, C. E., and Seufert, S. E., 1994, IEEE Trans. Nucl. Sci., NS-41(4), 1343.
- Hatsukade, I. and Tsunemi, H. 1992, Frontiers Science Series, Proceedings of the Yamada Conference XXVIII, held April 8-12, 1991, Aichi Sangyou Boueki Kaikan (Aichi Trade Center). Nagoya, Edited by Yasuo Tanaka and Katsuji Koyama. Japan, Tokyo, Japan: Universal Academy Press, 1992., p.387
- Hayashida, K., Inoue, H., Koyama, K., Awaki, H., and Takano, S. 1989, PASJ, 41, 373
- Henke, B.L., Gullikson, E.M., Davis, J.C., Atomic Data and Nuclear Data Tables Vol. 54 (no.2), 181-342 (July 1993). (http://www-cxro.lbl.gov:80/optical_constants/)
- Holt, S.S., Gotthelf, E.V., Tsunemi, H., Negoro, H. 1994, PASJ, 46, 151.

- Inoue, H., Koyama, K., Matsuoka, M., Ohashi, T., and Tanaka, Y. 1978, Nucl. Instr. Meth. A, 157, 295.
- Jahoda, K. and McCammon, D. 1988, Nucl. Instr. Meth. A, 272, 800.
- Jahoda, K., Swank, J. H., Giles, A. B., Stark, M. J., Strohmayer, T., Zhang, W., and Morgan, E. H. 1996, Proc. SPIE 2808: EUV, X-ray, and Gamma-ray Instrumentation for Astronomy VII, 59.
- Jahoda, K., Stark, M. J., Strohmayer, T. E., Zhang, W., Morgan, E. H., and Fox, D. 1999, Nuclear Physics B Proceedings Supplements. Eds. L. Scarsi, H. Bradt, P. Giommi, and F. Fiore, 69, 210.
- Kuulkers, E., den Hartog, P.R., in 't Zand, J.J.M., Verbunt, F.M.W., Harris, W.E., and Cocchi, M. 2003, A&A, 399, 663.
- Markwardt, C. B., Swank, J. H., Strohmayer, T. E., in't'Zand, J. J., and Marshall, F. E. 2002, ApJ, 575, L21.
- McMaster, W.H., Kerr Del Grande, N., Mallett, J.H., and Hubbell, J.H. 1969, Lawrence Livermore National Laboratory Report UCRL-50174 Section II Revision I (available from National Technical Information Services L-3, U.S. Dept. of Commerce or http://cars9.uchicago.edu/newville/mcbook/)
- Mighell, K.J., 1999, ApJ, 518, 380.
- Pravdo, S. H. and Smith, B. W. 1979, ApJ, 234, L195.
- Revnivtsev, M., Gilfanov, M., Sunyaev, R., Jahoda, K., and Markwardt, C. 2003, A&A, 411, 329.
- Rothschild, R.E., Boldt, E., Holt, S., Serlemitsos, P., Garmire, G., Agrawal, P., Riegler, G., Bowyer, S., and Lampton, M. 1979, Space Sci. Instr., 4, 269
- Rothschild, R. E., Blanco, P. R., Gruber, D. E., Heindl, W. A., MacDonald, D. R., Marsden, D. C., Pelling, M. R., and Wayne, L. R. 1997, ApJ, 496, 538.
- Rots, A.H., Jahoda, K., Macomb, D.J., Kawai, N., Saito, Y., Kaspi, V.M., Lyne, A.G., Manchester, R.N., Backer, D. C., Somer, A. L., Marsden, D. and Rothschild, R. E. 1998, ApJ, 501, 749.
- Saito, Y., Kawai, N., Rots, A., Kamae, T., and Shibata, S. 2001, New Century of X-ray Astronomy, ASP Conf Proc 251.

- Sosin, C. and King, I. R. 1995, AJ, 109, 639.
- Swank, J. and Markwardt, C., 2001. New Century of X-ray Astronomy, ASP Conf. Proc. v. 251, H. Inoue and H. Kuneida, eds., ISBN: 1-58381-091-9. San Francisco: Astronomical Society of the Pacific. p. 94.
- Tomsick, J. A. and Kaaret, P. 1998, http://lheawww.gsfc.nasa.gov/users/keith/tomsick_98.pdf
- Toor, A. and Seward, F.D. 1974, AJ, 79, 995
- Toor, A. and Seward, F.D. 1977, ApJ, 216, 560
- Tsunemi, H., Hayashida, K., Torii, K., Tamura, K., Miyata, E., Murakami, H., and Ueno, S., 1993, Nucl. Instr. Meth. A, 336, 301.
- Turner, M.J.L. et al., 1989, PASJ, 41, 345.
- Valinia, A. and Marshall, F.E., 1998, ApJ, 505, 134
- Youngen, J., Weisskopf, M.C., Dietz, K.L., Austin, R.A., O'Dell, S.L., Ramsey, B.D., and Tenant, A. 1994, Proc. SPIE, 2280, 145.
- Zhang, W., Morgan, E. H., Jahoda, K., Swank, J. H., Strohmayer, T. E., Jernigan, G., and Klein, R. I., 1996, ApJ, 469, L29.
- Zhang, W., Jahoda, K., Swank, J. H., Morgan, E. H., and Giles, A. B. 1995, ApJ, 449, 930.
- Zhang, W., Giles, A.B., Jahoda, K., Soong, Y., Swank, J.H., and Morgan, E.H. 1993, Proc SPIE, 2006, 324.
- Zombeck, M.V. 1990, "Handbook of Space Astronomy and Astrophysics", 2nd edition, Cambridge Univ. Press, Cambridge.

This preprint was prepared with the AAS IATEX macros v5.2.

A. Using PCA response matrix generator for user selected data modes

Creating a PCA response matrix involves creating 256 channel matrices suitable for each detector (pcarmf), shifting the channels following the EDS gain and offset description(rddescr, pcagainset, and gcorrmf), rebinning the channels to match the telemetered pulse height bins (rbnrmf), estimating the effective area of each detector after accounting for spacecraft pointing (xpcaarf), combining the area and redistribution matrices (marfrmf), and adding the matrices from the 5 PCU (addrmf). The perl script pcarsp takes care of these tasks. Section 3 described the contents and construction of pcarmf. The function and usage of the other tools are described in the help files. We describe the on-board gain shifting here.

The gain of each of the PCU detectors is similar, but not identical. Because it is often desirable to co-add data from the 5 detectors, to maximize time resolution within a given telemetry budget, the EDS does some channel shifting in order to add more nearly equivalent energies. The EDS does integer arithmetic, parameterized by a gain and offset, to shift the 256 input pulse height channels to 256 corrected pulse height channels. The gain term always results in an expansion, with the result that most channels are shifted upwards, but many pairs of adjacent original channels are shifted into corrected channels separated by two channels. The gain and offset parameters are not contained in the telemetry, but can be associated with the pulse height files with the ftool pcagainset. The channel shifting algorithm is

$$I_{corr} = \frac{(I_{orig} \times (256 + gain) + 128)}{256} + \text{offset}$$
(A1)

where I_{orig} is the pulse height produced by the PCU and I_{corr} is the corrected pulse height (Jahoda et al. 1996). Table 8 has the values of gain and offset parameters used throughout the RXTE mission.




Fig. 1.— Average number of eV required to create on electron-ion pair in Xenon as a function of incident photon energy. Data is from Dias et al. (1993).




Fig. 2.— Quantum efficiency for layers 1 (solid line), 2 (dashed), and 3 (dot-dash) of PCU 2 for 13 January 2002.




Fig. 3.— The model response is shown for 3 narrow input lines: at 5 keV where partial charge collection is important (solid line), at 9 keV where there is a small L-escape peak (dashed), and at 50 keV where there are prominent K-escape peaks (dot-dash).




Fig. 4.— Data and gaussian fits to the Am²⁴¹ calibration line collected in PCU 2 during sky background pointings in September 2000. The 60 keV peak is slightly assymetric as the Compton scattering cross section has become noticable (1.5% of the photo-electric cross section). We have ignored this effect.




Fig. 5.— Power-law plus gaussian fit to the Cas-A Fe line.




Fig. 6.— Ratio of model to data for Crab fit with a Xenon-free propane layer and the edge model described in the text (data points) and for the same continuum model with the optical depth set to 0 (line). The data is from 1997-12-20, PCU 2, layer 1.




Fig. 7.— Data and model for PCU 2, second layer, with a matrix that sets the total Xenon in layer 1 and the propane layer to 0. The primary edge has an optical depth of ~ 4 .




Fig. 8.— Best fit values for the areal density of Xenon in the top layer, second and third layers, dead layers, and propane layer. The dead layers between Xenon layers 1 and 2 and Xenon layers 2 and 3 is assumed to be the same. Our fits are consistent across the Epoch 3/4 boundary (day 457 on this scale). Only the amount of Xenon in the propane layer shows a time dependence; this is approximated as a linear trend in the response matrix generator.




Fig. 9.— Reduced χ^2 and photon index for PCU 2 observations of the Crab nebula on 15 March 2000 as a function of f. The broad minimum near f=0.4 is typical. The reduced χ^2 is dominated by remaining systematic errors near the Xenon L edges and in the lowest energy channels.




Fig. 10.— Energy fit to the Fe line in Cas-A. The model is described in section 4.1.2. Data from the different PCUs have been slightly offset in time for clarity. The best fit energy is quite close to the expected result of 6.59 keV.




Fig. 11.— The upper panel shows the photon index fit to data from the Crab for PCU 0. The crosses represent the Ftools v5.3 response generator with the default parameters (table 3) while the squares represent the previous calibration (Ftools v5.2). The lower panel shows the reduced χ^2 for each observation; the symbols have the same meaning. The success of the current calibration is demonstrated by the consistent measure of Γ with respect to time, and the good agreement between detectors. The previous parameterization gave slightly lower reduced χ^2 for some detectors, at the cost of greater detector to detector variability. For PCU 0, fits remain poor after the loss of the propane layer.




Fig. 12.— Same as figure 11, but for PCU 1.




Fig. 13.— Same as figure 11, but for PCU 2.




Fig. 14.— Same as figure 11, but for PCU 3.




Fig. 15.— Same as figure 15, but for PCU 4.




Fig. 16.— Power-law fits to a Crab monitoring observation for the first layers of the 5 PCUs. The lower panel shows the ratio of the data to the model.




Fig. 17.— Expanded view of the ratio in the lower panel of figure 16.




Fig. 18.— Contributions to χ^2 for the fits in figure 16. The reduced χ^2 is dominated by contributions from the lowest channels and the region near the Xenon L-edge.




Fig. 19.— Fits to three layers from PCU 2.




Fig. 20.— Pulse height spectra from PCU 2 obtained during observations of "blank" sky during May 1998. These spectra are the sum of Cosmic X-ray Background and unrejected instrument background. The spectra are collected separately for each layer; the solid line represents the first layer. The lower panel shows the fraction of the total rate due to the Cosmic X-ray background determined by differencing PCA observations of "blank" sky and dark earth (Revnivtsev et al. 2003).




Fig. 21.— The total background counting rate for one detector during a background monitoring campaign. The data are shown for all layers of PCU2. Large orbital variations are easily visible, as well as the effect of passages through the South Atlantic Anomaly. The large gaps are interruptions caused by observations of other sources. Also shown are the L7 and VLE rates, which are highly correlated with the blank sky rate and which are used to parameterize estimates of the instantaneous background.




Fig. 22.— The altitude of the RXTE orbit as a function of time. The orbit began to decay noticeably midway through epoch 3. The small time dependent background term, uncorrelated with the L7 rate, appears correlated and is probably physically associated with the orbit altitude.




Fig. 23.— Coincidence rate coefficients (B_i) of the background spectrum for PCU 2, layer 1, epoch 5. These coefficients are derived for the L7 model.




Fig. 24.— Accumulated radioactive dosage coefficients (C_i) of the background spectrum for PCU 2, layer 1, epoch 5. These coefficients are derived for the L7 model.




Fig. 25.— Unmodelled background variations. The upper line is plotted for 16 sec intervals, and is dominated by Poisson noise; the lower line is plotted for 1600 sec intervals, and is representative of the systematic uncertainties.




Fig. 26.— Crab rates as observed and corrected for deadtime. The lower panel shows the total deadtime from all sources. Also shown in the deadtime calculated from the "Very Large Event", "Remaining", and "Propane" rates as recorded in the Standard 1 data. The Very Large events make the largest contribution and the propane events the smallest. The total deadtime includes has a contribution from the source itself. The figure shows 3 on source intervals separated by observations of the earth. The deadtime induced by the Crab is comparable to the instrument background estimated from the occulted observations.




Fig. 27.— The collimator efficiency model for PCU 0. The vertical line represents a scan trajectory discussed in the text.




Fig. 28.— Data and model along a scan trajectory which passes near the peak of the response.




Fig. 29.— Ratio of residuals to the model. The collimator model is accurate to better than a few percent along the entire scan.




Fig. 30.— Differences between PCA derived positions of known sources and actual positions. The dark part of the offset is attributable to counting statistics; the remainder comes from source variability, ACS systematics, and inaccuracies in the collimator model.

Table 1. Nominal PCU Dimensions

component	Material	Dimension
Thermal shield	polyimide	76μ
Collimator sheet	BeCu	0.0027 inch
Collimator cell (height)		8 inch
Collimator cell (flat to flat)		0.125 inch
Entrance window	Mylar	0.001 inch
Window coating per side	Aluminum	70 nm
Anti-coincidence	Propane	$1.2~\mathrm{cm}$
pressure at $22 \deg C$		798 torr
Separation window	Mylar	0.001 inch
Window coating per side	Aluminum	70 nm
Main volume pressure at 22 deg C	Xenon $(90\%)/CH_4$ (10%)	836 torr
layer 1 depth		$1.35~\mathrm{cm}$
layer 2 depth		$1.20~\mathrm{cm}$
layer 3 depth		$1.20~\mathrm{cm}$
Inner shield	Tin	0.020 inch
Outer shield	Tantalum	0.060 inch

Table 2. High Voltage Epochs

Epoch	Start Date (UT)	PCU 0 HV	PCU 1 HV	PCU 2 HV	PCU 3 HV	PCU 4 HV
1 2	Launch 1996 March 21 @ 18:34	2030 2010	2030 2010	2026 2006	2027 2007	2048 2007
3A	1996 April 15 @ 23:06	1990	1990	1986	1987	1988
3B ^a 4 5 ^b	1998 February 9 @ 01:00 1999 March 22 @ 17:39 2000 May 12 @ 1:06 "	1970	1970	1966	1967 "	1968

^aEpochs 3A and 3B distinguish background models with different time dependence

 $^{^{\}rm b}{\rm PCU}$ 0 lost pressure in the propane volume at the beginning of Epoch 5

Table 3. Quantum efficiency and redistribution parameters - v5.3

parameter	PCU 0	PCU 1	PCU 2	PCU 3
$Xe_{l1} \ ({\rm gm} \ {\rm cm}^{-2})$	0.00663	0.00669	0.00692	0.00652
$Xe_{l2,3} \ ({\rm gm} \ {\rm cm}^{-2})$	0.00542	0.00556	0.00568	0.00526
$Xe_{pr} \ ({\rm gm} \ {\rm cm}^{-2} \ {\rm on} \ 1997 {\rm dec} 20)$	0.00015	0.00009	0.00013	0.00020
$Xe_{dl} \ (\mathrm{gm} \ \mathrm{cm}^{-2})$	0.00057	0.00062	0.00063	0.00071
Mylar (gm cm $^{-2}$ in 2 windows)	0.00699	0.00696	0.00695	0.00696
$d(Xe_{pr})/dt \text{ (gm cm}^{-2} \text{ day}^{-1})$	8.9E-08	5.2E-08	5.1E-08	4.7E-08
$Xe_{pr} \ ({\rm gm \ cm^{-2} \ on \ 2000 may 13})$	7.1E-05			
$d(Xe_{pr})/dt \text{ (gm cm}^{-2} \text{ day}^{-1})$	0.0E+00			
PCA Ur	niversal par	ameters		
$E_{point} \text{ (keV)}$			1.3E+01	
A_o			0.01677	
δ			2.90017	
$\kappa(5keV)$			0.043	
a (equation 6)			0.12100	
b (equation 6)			0.44200	
f (equation 2)			0.40000	
T_0 (equation 5)			"1997-12-20"	
K edge fration not self vetoed (section 3.3)			0.910	
L edge fraction not self vetoed (section 3.3)			1.000	
$Pr (gm cm^{-2})$			0.00261	
Al $(gm cm^{-2})$ total metal on 2 windows			0.00008	
K_{α} escape fraction			0.545	
K_{β} escape fraction			0.155	
L escape fraction (layer 1)			0.010	
electron offset, L escape			3.900	
electron offset, K_{α} escape			-2.260	
electron offset, K_{β} escape			3.840	

 ${\bf Geometric\ Areas\ (from\ {\tt xpcaarf.par})}$

Table 3—Continued

parameter	PCU 0	PCU 1	PCU 2	PCU 3	PCU 4
	17050	1.500.0	17000	1.001.0	4800.0
	1567.0	1536.0	1563.0	1631.0	1598.0

Table 4. In Flight calibration energies

Energy	Source
13.930	Np - L
17.530	Np - L
21.130	Np - L
26.350	Am^{241}
29.8	$Xe K_{\alpha} escape^{a}$
59.54	Am^{241}

^aBlend of Escape peak and Escape photon. Escape photon is occasionally reabsorbed in active volume while 59.54 keV photon is abasorbed in noninstrumented volume.

Table 5. Dedicated Blank Sky Pointing Directions

Target number ^a	α	δ
N0801-01	50.00	-67.00
N0801-02	60.00	20.00
N0801-03	138.00	15.00
N0801-04	235.00	10.00
N0801-05	345.00	18.00
N0801-06	160.00	72.57

The index N covers Announcement of Opportunity periods; complete description of the RXTE observation ids are given at

 $http://heasarc.gsfc.nasa.gov/docs/xte/start_guide.html\#directories_obid$

Table 6. Background Systematics^a

2-10 keV 3A 1 0.0289 0.82% 0.0300 0.82% 0.0250 0.68% 0.0254 0.76% 0.0332 3A 2 0.0101 0.91% 0.0170 1.56% 0.0168 1.51% 0.0161 1.50% 0.0191 3A 3 0.0173 1.56% 0.0215 1.99% 0.0439 3.83% 0.0163 1.58% 0.0211 3B 1 0.0277 0.79% 0.0357 0.98% 0.0285 0.78% 0.0349 1.06% 0.0420 3B 2 0.0185 1.71% 0.0160 1.52% 0.0172 1.59% 0.0177 1.69% 0.0209 3B 3 0.0179 1.65% 0.0185 1.77% 0.0360 3.27% 0.0312 0.88% 0.0209 4 1 0.0315 0.85% 0.0223 0.59% 0.0357 0.92% 0.0312 0.88% 0.0237 4 2 0.0127 1.10%	U 4
3A 1 0.0289 0.82% 0.0300 0.82% 0.0250 0.68% 0.0254 0.76% 0.0332 3A 2 0.0101 0.91% 0.0170 1.56% 0.0168 1.51% 0.0161 1.50% 0.0191 3A 3 0.0173 1.56% 0.0215 1.99% 0.0439 3.83% 0.0163 1.58% 0.0211 3B 1 0.0277 0.79% 0.0357 0.98% 0.0285 0.78% 0.0349 1.06% 0.0420 3B 2 0.0185 1.71% 0.0160 1.52% 0.0172 1.59% 0.0177 1.69% 0.0209 3B 3 0.0179 1.65% 0.0185 1.77% 0.0360 3.27% 0.0193 1.91% 0.0270 4 1 0.0315 0.85% 0.0223 0.59% 0.0357 0.92% 0.0312 0.88% 0.0237 4 2 0.0127 1.10% 0.0091 0.83% 0.	
3A 2 0.0101 0.91% 0.0170 1.56% 0.0168 1.51% 0.0161 1.50% 0.0191 3A 3 0.0173 1.56% 0.0215 1.99% 0.0439 3.83% 0.0163 1.58% 0.0211 3B 1 0.0277 0.79% 0.0357 0.98% 0.0285 0.78% 0.0349 1.06% 0.0420 3B 2 0.0185 1.71% 0.0160 1.52% 0.0172 1.59% 0.0177 1.69% 0.0209 3B 3 0.0179 1.65% 0.0185 1.77% 0.0360 3.27% 0.0193 1.91% 0.0270 4 1 0.0315 0.85% 0.0223 0.59% 0.0357 0.92% 0.0312 0.88% 0.0237 4 2 0.0127 1.10% 0.0091 0.83% 0.0149 1.30% 0.0112 1.02% 0.0116 4 3 0.0185 1.63% 0.0198 1.24% 0.0	0.0007
3A 3 0.0173 1.56% 0.0215 1.99% 0.0439 3.83% 0.0163 1.58% 0.0211 3B 1 0.0277 0.79% 0.0357 0.98% 0.0285 0.78% 0.0349 1.06% 0.0420 3B 2 0.0185 1.71% 0.0160 1.52% 0.0172 1.59% 0.0177 1.69% 0.0209 3B 3 0.0179 1.65% 0.0185 1.77% 0.0360 3.27% 0.0193 1.91% 0.0270 4 1 0.0315 0.85% 0.0223 0.59% 0.0357 0.92% 0.0312 0.88% 0.0237 4 2 0.0127 1.10% 0.0091 0.83% 0.0149 1.30% 0.0112 1.02% 0.0116 4 3 0.0185 1.63% 0.0198 1.03% 0.0253 2.23% 0.0164 1.58% 0.0110 5 1 0.01096 1.52% 0.0392 1.12% 0.0	0.88% $1.60%$
3B 1 0.0277 0.79% 0.0357 0.98% 0.0285 0.78% 0.0349 1.06% 0.0420 3B 2 0.0185 1.71% 0.0160 1.52% 0.0172 1.59% 0.0177 1.69% 0.0209 3B 3 0.0179 1.65% 0.0185 1.77% 0.0360 3.27% 0.0193 1.91% 0.0270 4 1 0.0315 0.85% 0.0223 0.59% 0.0357 0.92% 0.0312 0.88% 0.0237 4 2 0.0127 1.10% 0.0091 0.83% 0.0149 1.30% 0.0112 1.02% 0.0116 4 3 0.0185 1.63% 0.0108 1.03% 0.0253 2.23% 0.0164 1.58% 0.0110 5 1 0.1096 1.52% 0.0392 1.12% 0.0365 1.03% 0.0377 1.15% 0.0480 5 2 0.0123 1.64% 0.0119 1.38% 0.019	1.00% $1.77%$
3B 2 0.0185 1.71% 0.0160 1.52% 0.0172 1.59% 0.0177 1.69% 0.0209 3B 3 0.0179 1.65% 0.0185 1.77% 0.0360 3.27% 0.0193 1.91% 0.0270 4 1 0.0315 0.85% 0.0223 0.59% 0.0357 0.92% 0.0312 0.88% 0.0237 4 2 0.0127 1.10% 0.0091 0.83% 0.0149 1.30% 0.0112 1.02% 0.0116 4 3 0.0185 1.63% 0.0108 1.03% 0.0253 2.23% 0.0164 1.58% 0.0110 5 1 0.1096 1.52% 0.0392 1.12% 0.0365 1.03% 0.0370 1.15% 0.0480 5 2 0.0123 1.30% 0.0085 0.94% 0.0108 1.15% 0.0098 1.11% 0.0137 3A 1 0.0109 0.49% 0.0148 0.67% 0.013	1.11%
3B 3 0.0179 1.65% 0.0185 1.77% 0.0360 3.27% 0.0193 1.91% 0.0270 4 1 0.0315 0.85% 0.0223 0.59% 0.0357 0.92% 0.0312 0.88% 0.0237 4 2 0.0127 1.10% 0.0091 0.83% 0.0149 1.30% 0.0112 1.02% 0.0116 4 3 0.0185 1.63% 0.0108 1.03% 0.0253 2.23% 0.0164 1.58% 0.0110 5 1 0.1096 1.52% 0.0392 1.12% 0.0365 1.03% 0.0370 1.15% 0.0480 5 2 0.0123 1.30% 0.0085 0.94% 0.0108 1.15% 0.0098 1.11% 0.0137 5 3 0.0150 1.64% 0.0119 1.38% 0.0192 2.09% 0.0127 1.55% 0.0133 10-20 keV 1 0.0109 0.49% 0.0148 0.67% <td< td=""><td>1.75%</td></td<>	1.75%
4 1 0.0315 0.85% 0.0223 0.59% 0.0357 0.92% 0.0312 0.88% 0.0237 4 2 0.0127 1.10% 0.0091 0.83% 0.0149 1.30% 0.0112 1.02% 0.0116 4 3 0.0185 1.63% 0.0108 1.03% 0.0253 2.23% 0.0164 1.58% 0.0110 5 1 0.1096 1.52% 0.0392 1.12% 0.0365 1.03% 0.0370 1.15% 0.0480 5 2 0.0123 1.30% 0.0085 0.94% 0.0108 1.15% 0.0098 1.11% 0.0137 5 3 0.0150 1.64% 0.0119 1.38% 0.0192 2.09% 0.0127 1.55% 0.0133 10-20 keV 3 0.0109 0.49% 0.0148 0.67% 0.0130 0.59% 0.0119 0.56% 0.0133 3A 1 0.0109 0.76% 0.0081	$\frac{1.75\%}{2.29\%}$
4 2 0.0127 1.10% 0.0091 0.83% 0.0149 1.30% 0.0112 1.02% 0.0116 4 3 0.0185 1.63% 0.0108 1.03% 0.0253 2.23% 0.0164 1.58% 0.0110 5 1 0.1096 1.52% 0.0392 1.12% 0.0365 1.03% 0.0370 1.15% 0.0480 5 2 0.0123 1.30% 0.0085 0.94% 0.0108 1.15% 0.0098 1.11% 0.0137 5 3 0.0150 1.64% 0.0119 1.38% 0.0192 2.09% 0.0127 1.55% 0.0133 10-20 keV 10-20 keV 0.0148 0.67% 0.0130 0.59% 0.0119 0.56% 0.0133 3A 1 0.0109 0.49% 0.0048 0.68% 0.0131 1.13% 0.0081 0.78% 0.0123 3A 3 0.0114 1.04% 0.0139 1.24% 0.0127 1.10%	0.60%
4 3 0.0185 1.63% 0.0108 1.03% 0.0253 2.23% 0.0164 1.58% 0.0110 5 1 0.1096 1.52% 0.0392 1.12% 0.0365 1.03% 0.0370 1.15% 0.0480 5 2 0.0123 1.30% 0.0085 0.94% 0.0108 1.15% 0.0098 1.11% 0.0137 5 3 0.0150 1.64% 0.0119 1.38% 0.0192 2.09% 0.0127 1.55% 0.0133 10-20 keV 3 0.0109 0.49% 0.0148 0.67% 0.0130 0.59% 0.0119 0.56% 0.0133 3A 1 0.0109 0.49% 0.0148 0.67% 0.0130 0.59% 0.0119 0.56% 0.0137 3A 2 0.0090 0.76% 0.0081 0.68% 0.0131 1.13% 0.0114 1.20% 0.0130 3B 1 0.0084 0.38% 0.0076 0.35% </td <td>0.95%</td>	0.95%
5 1 0.1096 1.52% 0.0392 1.12% 0.0365 1.03% 0.0370 1.15% 0.0480 5 2 0.0123 1.30% 0.0085 0.94% 0.0108 1.15% 0.0098 1.11% 0.0137 5 3 0.0150 1.64% 0.0119 1.38% 0.0192 2.09% 0.0127 1.55% 0.0133 10-20 keV 3A 1 0.0109 0.49% 0.0148 0.67% 0.0130 0.59% 0.0119 0.56% 0.0137 3A 2 0.0090 0.76% 0.0081 0.68% 0.0131 1.13% 0.0081 0.78% 0.0092 3A 3 0.0114 1.04% 0.0139 1.24% 0.0127 1.10% 0.0114 1.20% 0.0130 3B 1 0.0084 0.38% 0.0076 0.35% 0.0125 0.57% 0.0120 0.57% 0.0085 3B 2 0.0074 0.63%	0.93%
5 2 0.0123 1.30% 0.0085 0.94% 0.0108 1.15% 0.0098 1.11% 0.0137 5 3 0.0150 1.64% 0.0119 1.38% 0.0192 2.09% 0.0127 1.55% 0.0133 10-20 keV 3A 1 0.0109 0.49% 0.0148 0.67% 0.0130 0.59% 0.0119 0.56% 0.0137 3A 2 0.0090 0.76% 0.0081 0.68% 0.0131 1.13% 0.0081 0.78% 0.0092 3A 3 0.0114 1.04% 0.0139 1.24% 0.0127 1.10% 0.0114 1.20% 0.0130 3B 1 0.0084 0.38% 0.0076 0.35% 0.0125 0.57% 0.0120 0.57% 0.0085 3B 2 0.0074 0.63% 0.0065 0.55% 0.0122 1.06% 0.0074 0.71% 0.0122 3B 3 0.0098 0.90% 0.0051 0.46% 0.0128 1.14% 0.0100 1.07% 0.0160 </td <td>1.35%</td>	1.35%
5 3 0.0150 1.64% 0.0119 1.38% 0.0192 2.09% 0.0127 1.55% 0.0133 3A 1 0.0109 0.49% 0.0148 0.67% 0.0130 0.59% 0.0119 0.56% 0.0137 3A 2 0.0090 0.76% 0.0081 0.68% 0.0131 1.13% 0.0081 0.78% 0.0092 3A 3 0.0114 1.04% 0.0139 1.24% 0.0127 1.10% 0.0114 1.20% 0.0130 3B 1 0.0084 0.38% 0.0076 0.35% 0.0125 0.57% 0.0120 0.57% 0.0085 3B 2 0.0074 0.63% 0.0065 0.55% 0.0122 1.06% 0.0074 0.71% 0.0127 3B 3 0.0098 0.90% 0.0051 0.46% 0.0122 1.06% 0.0074 0.71% 0.0122 4 1 0.0132 0.60% 0.0171 0.76% 0.0113 0.51% 0.0204 0.97% 0.0160 4 2 0.0097 0.74% 0.0106 0.77% 0.0080 0.61% 0.0141 1.26% 0.0125 4 3	1.39%
3A 1 0.0109 0.49% 0.0148 0.67% 0.0130 0.59% 0.0119 0.56% 0.0137 3A 2 0.0090 0.76% 0.0081 0.68% 0.0131 1.13% 0.0081 0.78% 0.0092 3A 3 0.0114 1.04% 0.0139 1.24% 0.0127 1.10% 0.0114 1.20% 0.0130 3B 1 0.0084 0.38% 0.0076 0.35% 0.0125 0.57% 0.0120 0.57% 0.0085 3B 2 0.0074 0.63% 0.0065 0.55% 0.0122 1.06% 0.0074 0.71% 0.0127 3B 3 0.0098 0.90% 0.0051 0.46% 0.0128 1.14% 0.0100 1.07% 0.0122 4 1 0.0132 0.60% 0.0171 0.76% 0.0113 0.51% 0.0204 0.97% 0.0160 4 2 0.0097 0.74% 0.0106 0.77% 0.0080 0.61% 0.0141 1.26% 0.0125 4 3 <td< td=""><td>1.42%</td></td<>	1.42%
3A 2 0.0090 0.76% 0.0081 0.68% 0.0131 1.13% 0.0081 0.78% 0.0092 3A 3 0.0114 1.04% 0.0139 1.24% 0.0127 1.10% 0.0114 1.20% 0.0130 3B 1 0.0084 0.38% 0.0076 0.35% 0.0125 0.57% 0.0120 0.57% 0.0085 3B 2 0.0074 0.63% 0.0065 0.55% 0.0122 1.06% 0.0074 0.71% 0.0127 3B 3 0.0098 0.90% 0.0051 0.46% 0.0128 1.14% 0.0100 1.07% 0.0122 4 1 0.0132 0.60% 0.0171 0.76% 0.0113 0.51% 0.0204 0.97% 0.0160 4 2 0.0097 0.74% 0.0106 0.77% 0.0080 0.61% 0.0115 0.96% 0.0125 4 3 0.0079 0.63% 0.0136 0.96% 0.0125 0.95% 0.0141 1.26% 0.0127	
3A 2 0.0090 0.76% 0.0081 0.68% 0.0131 1.13% 0.0081 0.78% 0.0092 3A 3 0.0114 1.04% 0.0139 1.24% 0.0127 1.10% 0.0114 1.20% 0.0130 3B 1 0.0084 0.38% 0.0076 0.35% 0.0125 0.57% 0.0120 0.57% 0.0085 3B 2 0.0074 0.63% 0.0065 0.55% 0.0122 1.06% 0.0074 0.71% 0.0127 3B 3 0.0098 0.90% 0.0051 0.46% 0.0128 1.14% 0.0100 1.07% 0.0122 4 1 0.0132 0.60% 0.0171 0.76% 0.0113 0.51% 0.0204 0.97% 0.0160 4 2 0.0097 0.74% 0.0106 0.77% 0.0080 0.61% 0.0115 0.96% 0.0125 4 3 0.0079 0.63% 0.0136 0.96% 0.0125 0.95% 0.0141 1.26% 0.0127	0.61%
3A 3 0.0114 1.04% 0.0139 1.24% 0.0127 1.10% 0.0114 1.20% 0.0130 3B 1 0.0084 0.38% 0.0076 0.35% 0.0125 0.57% 0.0120 0.57% 0.0085 3B 2 0.0074 0.63% 0.0065 0.55% 0.0122 1.06% 0.0074 0.71% 0.0127 3B 3 0.0098 0.90% 0.0051 0.46% 0.0128 1.14% 0.0100 1.07% 0.0122 4 1 0.0132 0.60% 0.0171 0.76% 0.0113 0.51% 0.0204 0.97% 0.0160 4 2 0.0097 0.74% 0.0106 0.77% 0.0080 0.61% 0.0115 0.96% 0.0125 4 3 0.0079 0.63% 0.0136 0.96% 0.0125 0.95% 0.0141 1.26% 0.0127	0.72%
3B 2 0.0074 0.63% 0.0065 0.55% 0.0122 1.06% 0.0074 0.71% 0.0127 3B 3 0.0098 0.90% 0.0051 0.46% 0.0128 1.14% 0.0100 1.07% 0.0122 4 1 0.0132 0.60% 0.0171 0.76% 0.0113 0.51% 0.0204 0.97% 0.0160 4 2 0.0097 0.74% 0.0106 0.77% 0.0080 0.61% 0.0115 0.96% 0.0125 4 3 0.0079 0.63% 0.0136 0.96% 0.0125 0.95% 0.0141 1.26% 0.0127	1.07%
3B 3 0.0098 0.90% 0.0051 0.46% 0.0128 1.14% 0.0100 1.07% 0.0122 4 1 0.0132 0.60% 0.0171 0.76% 0.0113 0.51% 0.0204 0.97% 0.0160 4 2 0.0097 0.74% 0.0106 0.77% 0.0080 0.61% 0.0115 0.96% 0.0125 4 3 0.0079 0.63% 0.0136 0.96% 0.0125 0.95% 0.0141 1.26% 0.0127	0.38%
4 1 0.0132 0.60% 0.0171 0.76% 0.0113 0.51% 0.0204 0.97% 0.0160 4 2 0.0097 0.74% 0.0106 0.77% 0.0080 0.61% 0.0115 0.96% 0.0125 4 3 0.0079 0.63% 0.0136 0.96% 0.0125 0.95% 0.0141 1.26% 0.0127	1.01%
4 2 0.0097 0.74% 0.0106 0.77% 0.0080 0.61% 0.0115 0.96% 0.0125 4 3 0.0079 0.63% 0.0136 0.96% 0.0125 0.95% 0.0141 1.26% 0.0127	1.01%
$4 \hspace{1.5cm} 3 \hspace{0.5cm} 0.0079 \hspace{0.2cm} 0.63\% \hspace{0.2cm} 0.0136 \hspace{0.2cm} 0.96\% \hspace{0.2cm} 0.0125 \hspace{0.2cm} 0.95\% \hspace{0.2cm} 0.0141 \hspace{0.2cm} 1.26\% \hspace{0.2cm} 0.0127$	0.70%
	0.89%
$5 \hspace{1.5cm} 1 \hspace{0.5cm} 0.0428 \hspace{0.2cm} 1.16\% \hspace{0.2cm} 0.0108 \hspace{0.2cm} 0.52\% \hspace{0.2cm} 0.0137 \hspace{0.2cm} 0.67\% \hspace{0.2cm} 0.0139 \hspace{0.2cm} 0.71\% \hspace{0.2cm} 0.0194$	0.92%
	0.92%
$5 \hspace{1.5cm} 2 \hspace{0.5cm} 0.0124 \hspace{0.2cm} 1.02\% \hspace{0.2cm} 0.0122 \hspace{0.2cm} 0.93\% \hspace{0.2cm} 0.0083 \hspace{0.2cm} 0.67\% \hspace{0.2cm} 0.0096 \hspace{0.2cm} 0.87\% \hspace{0.2cm} 0.0127$	0.98%
$5 \hspace{1.5cm} 3 \hspace{0.5cm} 0.0080 \hspace{0.2cm} 0.70\% \hspace{0.2cm} 0.0100 \hspace{0.2cm} 0.76\% \hspace{0.2cm} 0.0057 \hspace{0.2cm} 0.47\% \hspace{0.2cm} 0.0089 \hspace{0.2cm} 0.87\% \hspace{0.2cm} 0.0076$	0.60%

Table 6—Continued

Epoch Layer PCU 0 PCU 1 PCU 2 PCU 3 PCU 4

 $^{\rm a}{\rm The~Epoch~5}$ systematics are determined from data prior to November 2003

Table 7. Timing Error Budget

Description		Uncertainty (\sim 99%; μ s)
Electron Drift GoodXenon EDS Timestamp RXTE Clock Model MOC Variance ^a White Sands Station UTC(GPS) - TT(BIPM) TT - TDB	$\sigma_{ m drift}$ $\sigma_{ m EDS}$ $\sigma_{ m model}$ $\sigma_{ m var}$ $\sigma_{ m WS}$ $\sigma_{ m GPS}$	<1 1 2.5 4.4 1 0.1 0.023
Satellite Ephemeris	$\sigma_{ m eph}$	1.5

 $^{^{\}rm a}{\rm Applies}$ to observations preceding MJD 50,567

Table 8. Gain and offset values for the PCA

Date	PC	CU 0	PC	U 1	PC	CU 2	PC	U 3	PC	CU 4
	gain	offset								
12/30/95:00:00:00 ^a	24	1	22	1	29	1	10	0	2	0
01/18/96:18:31:45	0	0	0	0	0	0	0	0	0	0
02/28/96:19:24:40	29	-1	20	-1	27	-1	14	-1	-1	-1
03/25/96:21:02:50	29	-1	20	-1	27	-1	14	-1	33	-1

^afirst data and time for which these settings apply

Table 9. PCU alignements

PCU	y(RXTE)	z(RXTE)
0	-0.0000385	0.000629
1	0.0001046	0.000529
2	-0.0000500	0.000746
3	0.0002940	0.001340
4	0.0002900	0.001970
RXTE ^a	0.0000000	0.000700

^aThe science axis is controlled by pointing commands to the space-craft

Table 10. PCA Position Measurements for 4U 1820-30

PCU	observations	$< \alpha > (J2000)$ (J2000)	$<\delta>$ (J2000) (J2000)	$\Delta\theta$ (arcsec) (arcsec)	$\Delta\theta_{stat} \text{ (arcsec)}$ (arcsec)
0	208	275.9196°	-30.3617°	3.83	1.63
1	22	275.9205°	-30.3638°	11.34	5.46
2	212	275.9196°	-30.3601°	4.67	1.65
3	186	275.9181°	-30.3602°	2.20	1.75
4	45	275.9219°	-30.3616°	10.38	3.90